

GREEN POWER GP110S/I SOUNDPROOF (MANUAL CONTROL UNIT)



Product price:

14.798,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 88

Continuous power three phase (KW): 80

Maximum power three phase (KVA): 110

Continuous power three phase (KVA): 100

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: PERKINS 1104C-44TAG2, 4 stroke turbo-aftercooler

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4500

Number cylinders: 4
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22SD/4 - Sincrono
Poles: 4
Fuel tank capacity (L): 140
Consumption (L/h): 16.2 at 75% of the load
Running time (h): 9.62 h al 75% del carico
Length (mm): 2850
Width (mm): 1000
Height (mm): 1400
Dry weight (Kg): 1650
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR