



# GREEN POWER GP700S/C SOUNDPROOF (MANUAL CONTROL UNIT)

Product price:

**93.067,00 € tax excluded**

## Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**QUESTO PRODOTTO È DISPONIBILE SOLO NELLA VERSIONE CENTRALINA AUTOMATICA**

## È possibile scegliere tra le versioni:

- Gruppo super silenziato con alternatore AVR-Leroy (centralina automatica)
- Gruppo super silenziato con alternatore AVR-Mecc alte (centralina automatica)
- Gruppo super silenziato con alternatore AVR-Stamford (centralina automatica)

The image is purely indicative.



**Product features:**

Phase: Three phase  
Maximum power three phase (KW): 396  
Continuous power three phase (KW): 480  
Maximum power three phase (KVA): 495  
Continuous power three phase (KVA): 600  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: 1506A-E88TAG2  
Emissions Regulations: NON EMISSIONATO  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 8800  
Number cylinders: 6  
Cylinders' position: In line  
Cooling: Water  
Alternator: LINZ PRO 22SD/4 - Sincrono  
Poles: 4  
Protection degree: IP23  
Fuel tank capacity (L): 490  
Consumption (L/h): 24.7 Lt/h al 75% del carico  
Running time (h): 9.62 h al 75% del carico  
Acoustic pressure: 69 dB(A)  
Length (mm): 5000  
Width (mm): 1900  
Height (mm): 2350  
Dry weight (Kg): 7300  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR