

NO

GREEN POWER GP880A/C OPEN (MANUAL CONTROL UNIT)

Product price:

101.504,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose between the versions:

-Open group with AVR-Leroy alternator (automatic power pack)

-Open group with AVR-Mecc Alte alternator (automatic power pack)

-Open group with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

R

Product features:

Ø.

Phase: Three phase Maximum power three phase (KW): 704 Continuous power three phase (KW): 640 Maximum power three phase (KVA): 880 Continuous power three phase (KVA): 800 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 230 / 400 Engine: CUMMINSQSK23G3 **Emissions Regulations: NON EMISSIONATO** Engine rpm (rpm): 1500 Speed governor: Electronic Starting system: Elettrico Engine capacity (cm³): 23150 Number cylinders: 6 Cylinders' position: In line Cooling: Water Alternator: LINZ PRO 22SD/4 - Sincrono Poles: 4 Protection degree: IP23 Fuel tank capacity (L): 400 Consumption (L/h): 121 Lt/h al 75% del carico Running time (h): 9.62 h al 75% del carico Length (mm): 4000 Width (mm): 1700 Height (mm): 2100 Dry weight (Kg): 3430 Silenced: No Super silenced: No ATS Switch device : Optional Voltage regulator: AVR