



GREEN POWER GP6A/KW-C OPEN WITH (MANUAL CONTROL UNIT)

Product price:

5.086,00 € tax excluded

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose between several versions:

-Silenced unit with Compound-Linz alternator (automatic power pack)

-Silenced unit with AVR-Linz alternator (automatic control unit)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 4.4



Continuous power three phase (KW): 4
Maximum power three phase (KVA): 5.5
Continuous power three phase (KVA): 5
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: Kohler KDW 702
Emissions Regulations: Non Emissionati
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Elettrico
Engine capacity (cm³): 686
Number cylinders: 2
Cylinders' position: In line
Cooling: Water
Alternator: LINZ E1S13S A/4
Poles: 4
Protection degree: IP21
Fuel tank capacity (L): 55
Consumption (L/h): 1.2 al 75% del carico
Running time (h): 45 al 75% del carico
Length (mm): 1300
Width (mm): 700
Height (mm): 1000
Dry weight (Kg):
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: Compound / AVR (optional)