



GREEN POWER GP66A/K-N OPEN (MANUAL CONTROL UNIT)

Product price:

11.234,00 € tax excluded

Product description:

GREEN POWER GP66A/K-N OPEN (MANUAL CONTROL UNIT)

Introducing the GREEN POWER GP66A/K-N, an open configuration power unit equipped with a manual control system. Crafted for those who value direct control and reliability, this unit boasts exceptional performance and versatility. Its open design ensures easy accessibility, while the manual control unit offers straightforward operation. Experience the synergy of power and precision with the GREEN POWER GP66A/K-N.

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose between the versions:

-Open group with AVR-Leroy alternator (automatic power pack)

-Open group with AVR-Mecc Alte alternator (automatic power pack)

-Open genset with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 54.4

Continuous power three phase (KW): 49.6

Maximum power three phase (KVA): 68

Continuous power three phase (KVA): 62

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Kohler KDI3404TM

Emissions Regulations: Non Emissionati

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 3359

Number cylinders: 4

Cylinders' position: In line

Cooling: Water

Alternator: LINZ PRO 18LG/4 - Sincrono

Poles: 4

Fuel tank capacity (L): 100

Consumption (L/h): 11.3 al 75% del carico

Running time (h): 8.84 h al 75% del carico

Length (mm): 2100

Width (mm): 700

Height (mm): 1300

Dry weight (Kg): 910

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR