



GREEN POWER GP610A/DO-N OPEN (MANUAL CONTROL UNIT)

Product price:

47.802,00 € tax excluded

Product description:

GREEN POWER GP610A/DO-N OPEN (MANUAL CONTROL UNIT)

Discover the GREEN POWER GP610A/DO-N, a robust and efficient open power unit tailored for those who prefer manual control. With its user-friendly manual control unit, you can harness the power with precision and ease. Whether you're on a job site or in a remote location, this unit ensures you have reliable energy at your fingertips.

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose between the versions:

-Open group with AVR-Leroy alternator (automatic power pack)

-Open group with AVR-Mecc Alte alternator (automatic power pack)

-Open genset with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 484

Continuous power three phase (KW): 440

Maximum power three phase (KVA): 605

Continuous power three phase (KVA): 550

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: DOOSAN DP180LA

Emissions Regulations: Non Emissionati

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm³): 18273

Number cylinders: 10

Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTEECO40 1L/4

Poles: 4

Fuel tank capacity (L): 320

Consumption (L/h): 24.7 Lt/h al 75% del carico

Running time (h): 9.62 h al 75% del carico

Length (mm): 3400

Width (mm): 1400

Height (mm): 2100

Dry weight (Kg): 3430

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR