



GREEN POWER GP650S/V SOUNDPROOF (MANUAL CONTROL UNIT)

Product price:

66.600,00 € tax excluded

Product description:

GREEN POWER GP650S/V SOUNDPROOF (MANUAL CONTROL UNIT)

Introducing the GREEN POWER GP650S/V, a pinnacle of soundproofing technology combined with user-friendly manual control. Designed to operate with minimal noise, this unit epitomizes GREEN POWER's commitment to innovative solutions that meet modern demands. Whether in a residential or commercial setting, the GP650S/V ensures a quiet operation without compromising on performance or reliability. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION

You can choose between the versions:

-Silenced group with AVR-Leroy alternator (automatic power pack)



-Silenced group with high AVR-Mecc alternator (automatic control unit)

-Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 520

Continuous power three phase (KW): 472

Maximum power three phase (KVA): 650

Continuous power three phase (KVA): 590

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Emissions Regulations: Stage 2

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Number cylinders: 6

Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTE ECO40 1.5L/4

Poles: 4

Consumption (L/h): 88 Lt/h al 75% del carico

Running time (h): 4.65 h al 75% del carico

Length (mm): 4500

Width (mm): 1450

Dry weight (Kg): 5100

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

