



# GENMAC ATS-M 4P 50-60Hz 3PH 380..400V 200A

**Product price:**

**1.091,00 € tax excluded**

## **Product description:**

The Panels ATS-C and ATS-M are Automatic Transfer Switches for mains/ generator changeover and are made in order to be connected to Genmac generators manufactured in A-Automatic version, this means equipped with battery charger and AMF controller on board. The panels are realized into a metal box with high

protection degree painted with powder coats Ral 7035. The components used are of high quality and tested under severe conditions in order to grant high number of cycles.

ATS-C panels (Automatic Transfer Switch Contactors) are supplied with Contactors, Lovato Brand, mechanically and electrically interlocked. Manual forced opening of the contactor is Not possible on this series. Power connections can be made trough a terminal block (adequately sized for the maximum power).

ATS-M panels (Automatic Transfer Switch Motorized) are supplied with Motorized Changeover Switches ABB Brand, mechanically and electrically interlocked. Manual forced opening of the contactor is possible on this series trough a suitable lever supplied. Power connections can be made trough a copper bus bar (adequately sized for the maximum power).

Standard Composition

- Metal Box
- Terminal block for Auxiliary circuit cable connections
- Industrial protection fuses
- Signalling light for switching status
- Lock with key
- Bottom plate removable
- Wall-mounting accessories (up to 400A 3ph)
- Power terminal blocks (ATS-C )
- Copper bus bar for power connections (ATS-M)
- Interlocked Contactors (ATS-C )



- Interlocked Motorized changeover switches (ATS-M)

Standards

CEI 1713-1 EN 60439-1, CEI 17-43, CEI 17-52

Reference conditions for declared performances\*

- Temperature From  $-10^{\circ}\text{C}$  to  $+35^{\circ}\text{C}$

- Altitude \* For usage at temperatures higher than  $+ 35^{\circ}\text{C}$  please check derating factors into technical documentation. For usage at temperatures lower than

$-10^{\circ}\text{C}$  please

**Product features:**

Protection degree: IP65

Length (mm): 300

Width (mm): 600

Height (mm): 800

Product type: Switching Frame

Weight (Kg): 41

