



# GREEN POWER GP1650SM/MI SOUNDPROOF (MANUAL CONTROL UNIT)

**Product price:**

**235.045,00 € tax excluded**

## **Product description:**

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE AUTOMATIC CONTROL UNIT VERSION**

## **You can choose between the versions:**

- Silenced group with AVR-Leroy alternator (automatic power pack)
- Silenced group with high AVR-Mecc alternator (automatic control unit)
- Silenced group with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.



**Product features:**

Phase: Three phase

Maximum power three phase (KW): 1320

Continuous power three phase (KW): 1120

Maximum power three phase (KVA): 1650

Continuous power three phase (KVA): 1400

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: 1506A-E88TAG2

Emissions Regulations: Non Emissionati

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm<sup>3</sup>): 49030

Number cylinders: 12

Cylinders' position: In line

Cooling: Water

Alternator: MECC ALTE ECO43 VL/4

Poles: 4

Fuel tank capacity (L): 670

Consumption (L/h): 222 al 75% del carico

Running time (h): 3 al 75% del carico

Acoustic pressure: 75 dB(A)

Length (mm): 7000

Width (mm): 2270

Height (mm): 2550

Dry weight (Kg): 16000

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: AVR

