



# GREEN POWER GP44SH/DW SOUNDPROOF (MANUAL CONTROL UNIT)

Product price:

**10.762,00 € tax excluded**

## Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

**THIS PRODUCT IS ONLY AVAILABLE IN THE 'AUTOMATIC CONTROL UNIT' VERSION.**

## You can choose between the versions indicated:

- Super soundproof with AVR-Leroy alternator (automatic control unit)
- Super soundproof with AVR-Mecc alte alternator (automatic control unit)
- Super soundproof with AVR-Stamford alternator (automatic control unit)

The image is purely indicative.

## Product features:

Phase: Three phase

Maximum power three phase (KW): 35.2

Continuous power three phase (KW): 32

Maximum power three phase (KVA): 44

---

Continuous power three phase (KVA): 40  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: DEUTZ BF4M2011  
Emissions Regulations: Stage 2  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Elettrico  
Engine capacity (cm<sup>3</sup>): 3108  
Number cylinders: 3  
Cylinders' position: In line  
Cooling: Oil  
Alternator: MECC ALTE ECP32 2S/4  
Poles: 4  
Fuel tank capacity (L): 70  
Consumption (L/h): 7.1 al 75% del carico  
Running time (h): 9.5 at 75% of the load  
Length (mm): 1850  
Width (mm): 700  
Height (mm): 1020  
Dry weight (Kg): 98  
Silenced: Yes  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR  
Power factor control: 0.8