



GREEN POWER GP165A/D OPEN (MANUAL CONTROL UNIT)

Product description:

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 132

Continuous power three phase (KW): 120

Maximum power three phase (KVA): 165

Continuous power three phase (KVA): 150

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: DEUTZBF6M 1013EC

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 7146
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22MF/4
Poles: 4
Fuel tank capacity (L): 125
Consumption (L/h): 23.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Length (mm): 2500
Width (mm): 1000
Height (mm): 1400
Dry weight (Kg): 1730
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR