



GREEN POWER GP220S/D SOUNDPROOF (AUTOMATIC CONTROL UNIT)



Product price:

25.819,00 € tax excluded

Product description:

GREEN POWER GP220S/D SOUNDPROOF (AUTOMATIC CONTROL UNIT)

Introducing the GREEN POWER GP220S/D with soundproof design, crafted to provide a noise-reduced operational experience. Equipped with an automatic control unit, this model ensures efficient power management with minimal manual intervention. Embodying GREEN POWER's commitment to innovation and user convenience, this product delivers both performance and peace of mind in noise-sensitive environments. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 176



Continuous power three phase (KW): 160
Maximum power three phase (KVA): 220
Continuous power three phase (KVA): 200
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: FPT N67TE2A
Engine rpm (rpm): 1500
Speed governor: Electronic
Starting system: Elettrico
Engine capacity (cm³): 7146
Number cylinders: 6
Cylinders' position: In line
Cooling: Water
Alternator: LINZ PRO 22SD/4 - Sincrono
Poles: 4
Fuel tank capacity (L): 125
Consumption (L/h): 24.7 Lt/h al 75% del carico
Running time (h): 9.62 h al 75% del carico
Acoustic pressure: 68 dB(A)
Length (mm): 1300
Width (mm): 1100
Height (mm): 1770
Dry weight (Kg): 2250
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR