



IDROFOGLIA MK50-150-SP SELF- PRIMING CENTRIFUGAL PUMP WITH ROAD TRAILER

Product description:

IDROFOGLIA MK50-150-SP SELF-PRIMING MOTORPUMP WITH ROAD TOWING TROLLEY

IDROFOGLIA MK50-150-SP is a self-priming centrifugal motorpump used for land drainage and any other water and bentonite sludge handling operations.

Water pumping with sand or gravel is possible thanks to the robustness of the hydraulics and the wide passage of solids.

IDROFOGLIA MK50-150-SP is equipped with Elcos CEP 090 control unit, with engine protection for insufficient oil pressure, overtemperature, belt breakage (lack of battery recharge), minimum fuel level. Starting by key. On-screen display of hour meter, rev counter, fuel level, battery voltmeter.

The motorpump IDROFOGLIA MK50-150-SP is mounted on a road trolley that allows its safe transport.

IDROFOGLIA MK50-150-SP is composed of:

Kohler engine mod. 2504M + Mill.ar self-priming pump with 6" / Ø150 ports

SEL0001136 ACC. MTA LIFTING BRIDGE WITH ROOF (T3-T3A)

SEL0001098 FERRARI M-UNION WITH FLANGE Ø150x6"

HOMOLOGATED ROAD TROLLEY UK1800

SEL0001098 SELF-PRIMING MOTORPUMP

Suction diameter: Ø 150 (6")

Diameter discharge: Ø 150 (6")

Maximum flow rate: 5. 400 lt/min

Maximum head: 38 mt

Maximum suction: -8 m
Solids passage: 76 mm
Power consumption: 22 kW (29.9 hp)
Rotation speed: 1. 800 rpm
Impeller diameter: 256 mm
Impeller blades: Nr. 3

Motorpump body: Grey cast iron EN JGL 250
Impeller: Spheroidal cast iron
Wear plates: Spheroidal cast iron
Mechanical seal: Widia
Impeller shaft: Steel [39 NcD4]
Coupling: Elastic coupling
Liquid temperature: 55 °C
Liquid density: 1.250 kg/m³

DIESEL ENGINE

Manufacturer: Kohler 2504 M
Displacement: 2.482 cc
Power: 36,4 kW (49,5 hp)
Number of cylinders: 4
Cooling: Liquid
Max speed: 2.600 rpm
Max consumption: 10,02 lt/h
Fuel tank capacity: 150 lt

Are you looking for a motorpump with different characteristics? Here you can find the entire range of IDROFOGLIA or other brands specializing in the field.

Images and technical data are not binding and may be subject to revision by the supplier.

Product features:

Fuel: Diesel
Engine: Kohler KDI 2504 M
Emissions Regulations: STAGE III A
Starting system: Electric
Engine capacity (cm³): 2482
Number cylinders: 4
Cooling: Coolant Liquid
Pump type: High flow rate pump
Fluid type: Dirty water
Height of suction (m): 8

Maximum output capacity (Lt/min): 5400
Input power (W): 22
Main body material: Cast iron EN JGL 250
Number of wheels: 2
Inlet diameter thread type (mm/inches): Ø 150 / 6"
Outlet diameter thread type (mm/inches): Ø 150 / 6"
Debris size capacity (mm): 76
Total head (m): 38
Mechanical power (hp): 49.5
Transportability: Fast Trailer
Fuel tank capacity (L): 150
Consumption (L/h): 10
Running time (h): 15 at 100% of the load
Engine manufacturer: Kohler