



TF51 LIGHTING TOWER

4x100W LED

Product price:

3.928,00 € tax excluded

Product description:

TF50 TORRE FARO LIGHT STANDARD 4x100W LED

The STANDARD columns are produced starting from a \varnothing of 115 mm with heights ranging from 2.7 m up to 11 m with 4,5, 6, 7 extensions.

These columns are ideal for mounting on medium/large vehicles with various types of headlamps. We offer a wide range of internal spiral cables, especially for 4,5,6 extension columns.

Telescopic pneumatic column in grey anodized aluminium
standard MANUALLY STANDARD REVOLUTIONS \varnothing 115 mm 5 extensions complete with anti-rotation pads on each extension, handwheel for manual rotation of the column and internal spiral cable:

- Maximum height of the extension column: 9223 mm
- Minimum height of closed column: 2216 mm
- Maximum sustainable load of the column with centre weight: 40 kg
- Maximum SURVIVOR resistance to wind: 90 Km/h with surface 0,3 m²
- Inner spiral cable: 8 x 1.0 + 4 x 0.5mm² or equivalent
- Column weight: 37,4 Kg CIRCA
- Last section \varnothing : 51 mm

Mechanical micro-switch for signalling of the extended column.

Bracket for external fixing UPPER columns \varnothing 115 mm to the wall.

Bracket for external LOWER fixing (base) of \varnothing 115 mm columns to the wall.

SPECIAL long stroke hand pump complete with safety vent valve and oversized PVC handle.
2m hose for column pump connection.

2x Brackets for fixing the pump to the wall by hand.

Head holder 4x100W LED 230V IP65 cod. complete
of bracket with headlights mounted for pointing, wired.



Weight: 12Kg

Exposed area: 0.18m²

The image is purely indicative.

Product features:

Phase: Single phase

Frequency (Hz): 50

Voltage (V): 230

Protection degree: IP65

Main body material: Aluminium

Type of lamps: LED

Lamps: 4 x 100 W

Telescopic pole: Aluminum

Total lumens (Lm): 61000

Lifting System: Manual lifting system

Maximum height (m): 9

Mast rotation: 360°

Height closed (mm): 2216

With generator / Without generator: Without generator

Transportability: Stationary

Stability to wind (Km/h): 90

Outer diameter (mm): 115

Weight (Kg): 57