



VICTRON MultiPlus 24/500/10-16 Battery Charger Inverter 24V 16A

Product price:

360,00 € tax excluded

Product description:

VICTRON MultiPlus 24/500/10-16 24V 16A BatteryCharger Inverter

The VICTRON MultiPlus 24/500/10-16 is a powerful pure sine wave inverter and battery charger with adaptive charging technology and a high-speed AC transfer switch.

The VICTRON MultiPlus 24/500/10-16 is a versatile solution that offers a wide range of advanced features for supply and energy management. This model supports parallel operation and can be configured to operate in a three-phase mode, allowing users to connect up to six MultiPlus units for a significant improvement in power output. This parallel connection capability provides flexibility in managing energy demands.

One of the key features of the VICTRON MultiPlus 24/500/10-16 battery charger is the PowerControl technology, which allows setting a maximum current limit for the generator or shore connection. This effectively prevents overload of these power sources when other AC loads are in operation.

PowerAssist is an innovative aspect that enables integrating power from alternative sources during peak energy demand periods. This ensures an uninterrupted energy flow, keeping operations smooth even during moments of high power demand.

Equipped with an advanced four-stage adaptive charging process, the VICTRON battery charger is capable of optimizing battery charging and maintenance, enhancing their longevity over time. The Search mode is designed to improve the inverter's energy efficiency during idle operation, reducing energy consumption by up to 70%. The programmable relay acts as an alarm trigger, deactivating in case of abnormal conditions such as high inverter temperatures, excessive input ripple, or insufficient battery voltage.

With remote control capability, the VICTRON MultiPlus 24/500/10-16 allows managing the inverter, battery charger, and ignition/shutdown functions through a three-pole connector. The

design aims to simplify configuration, monitoring, and control after installation, with the possibility of adjusting some settings via DIP switches.

For advanced remote monitoring and control, the installation of a Cerbo GX or other GX products connected to the Internet allows access to operational data through the Victron Remote Management (VRM) platform, offering more comprehensive and informed management of inverter performance.

TECHNICAL SPECIFICATIONS VICTRON MultiPlus 24/500/10-16

PowerControl: No

Parallel and Three-Phase Operation: Yes

Transfer Switch: 16A

INVERTER

Input Voltage Range: 9.5 – 17 V

Output Voltage: 230 VAC \pm 2%

Frequency: 50 Hz \pm 0.1%

Continuous Output at 25°C: 500 VA

Continuous Output at 25° / 40° / 65°: 430 W / 400 W / 300W

Peak Power: 900 W

Maximum Efficiency: 91%

Zero Load supply Consumption: 6 W

Zero Load supply Consumption in Search Mode: 2 W

BATTERYCHARGER

Input Voltage Range: 187-265 VAC

Input Frequency: 45-65Hz

"Absorption" Charge Voltage: 28.8 V

"Float" Charge Voltage: 27.6 V

"Storage" Mode Voltage: 26.4 V

Service Battery Charge Current: 10 A

Battery Charge Current: 1 A

Battery Temperature Sensor: Yes

Width: 182 mm

Length: 100 mm

Height: 311 mm

Weight: 4.4 kg

Looking for a product with different technical specifications? Here you can find the complete range of VICTRON batterychargers and inverters, as well as other specialized brands.

Images and technical data are not binding.



Product features:

Phase: Single phase

Frequency (Hz): 50 / 60

Voltage (V): 187-265

Protection degree: IP21

Output voltage (V): 230

Nominal current (A): 28.8

Charging voltage (V): 24

Length (mm): 311

Width (mm): 182

Height (mm): 100

Overload protectors: Yes

Input voltage (V): 24

Kind of wave: Pure Sinusoidal

Continuous power (W): 500

Colour: Blue

Weight (Kg): 4.5

