



# GENMAC Daily-GAS G5900HS LPG GENERATOR 6,6KVA

**Product price:**

**3.476,00 € tax excluded**

## **Product description:**

GENMAC DAILY-GAS G5900HS LPG THREE-PHASE GENERATOR 6.6KVA

The Genmac Daily-GAS G5900HS LPG three-phase generator is equipped with a Honda engine powered by LPG gas capable of delivering a power of 6.6KVA with capacitor voltage regulator (AVR optional).

High quality professional silenced three-phase LPG power generator, Genmac with 6.6KVA power. The Genmac LPG generator is equipped with an oversized air-cooled Honda engine.

Genmac professional LPG generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

This feature is fundamental to guarantee a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

All Honda engines are built using the best materials, the most innovative techniques and the most advanced methods for quality control.

The 6.6KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

## AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving performance and durability.

The model equipped with AVR board is highly recommended, as it guarantees a significant

improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

#### TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily-GAS G5900HS LPG 6,6KVA

Voltage regulator : capacitor (AVR Optional)

Power supply: LPG

Firing: Electric

Phase type: Single phase / Three phase

Single phase continuous power: 2KVA / 1.8KW

Maximum single phase power: 2. 2KVA / 2KW

Three-Phase Continuous Power: 5.9KVA / 4.7KW

Three-Phase Maximum Power: 6.6KVA / 5.3KW

Motor: Honda GX390

Socket Frame: 1 x 16A 230V / 1 x 32A 230V / 1 x 16A 400V

Voltage: 230 / 400 V

Frequency: 50 Hz

3000 turns per minute

Autonomy @ 75%: 1.64 h fixed turns

Acoustic pressure: 62 dB(A) @ 7m

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 183

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

#### Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 2

Continuous power single phase (KW): 1.8

Maximum power single phase (KVA): 2.2

Continuous power single phase (KVA): 2

Maximum power three phase (KW): 5.3

Continuous power three phase (KW): 4.7

Maximum power three phase (KVA): 6.6

---

Continuous power three phase (KVA): 5.9  
Fuel: LPG  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 16A 230V / 1 x 32A 230V / 1 x 16A 400V  
Engine: Honda GX390  
Engine rpm (rpm): 3000  
Speed governor: Mechanical  
Starting system: Electric  
Cooling: Air  
Poles: 2  
Consumption (L/h): 1.64 mc./h al 75%  
Acoustic pressure: 62 dB(A) at 7 m  
Length (mm): 1030  
Width (mm): 620  
Height (mm): 804  
Dry weight (Kg): 183  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Honda