



PRAMAC LIFTER SCALE TRUCK PX25

Product price:

1.310,00 € tax excluded

Product description:

The scale trucks range are equipped with a functional and precise weighing device with several operating options, suitable for lifting heavy loads.

Display

The PX20 pallet truck is a simple, economical and robust tool to be used for the weighing of transported loads. Its large-sized LCD display allows for easy reading of weight and the setting of tare simply and immediately.

Frame structure

The structure is made up of a double frame and a lower fork on which a counter fork is placed; both forks house four load cells that allow for a uniform load distribution, thus keeping weighing precision even in case of collision and unbalanced load.

The images are purely indicative.

Product features:

Drive: Manual

Operator type: Pedestrian

Load capacity (Kg): 2500

Load centre distance (mm): 600

Load axle to end forks (mm): 975

Wheel base (mm): 1250





Service weight (Kg): 113
Axle load, laden rear (Kg): 1830
Axle load, laden front (Kg): 783
Axle load, unladen front (Kg): 71
Axle load, unladen rear (Kg): 42
Tyres: front wheels: POLY.C
Tyres: rear wheels: POLY.I.
Diameter steering wheels (mm): 200
Width steering wheels (mm): 55
Diameter load rollers (mm): 82
Width load rollers (mm): 60
Quantity rear wheels: 4
Quantity front wheels: 2
Rear balancing axle: No
Tread front (mm): 155
Tread rear (mm): 375
Lift height (mm): 115
Height of tiller in drive position max (mm): 1160
Height of tiller in drive position min (mm): 690
Height lowered (mm): 90
Overall length (mm): 1596
Length to face of forks (mm): 411
Overall width (mm): 555
Thickness fork (mm): 60
Width fork (mm): 180
Length fork (mm): 1185
Distance between fork arms (mm): 555
Ground clearance at centre of wheelbase (mm): 30
Aisle width (mm): 1851
Turning radius (mm): 1426
Lifting speed laden (strokes): 13
Lifting speed unladen (strokes): 13
Lowering speed laden (m/s): 0.05
Lowering speed unladen (m/s): 0.02
Weigher: Yes

