

# TELAIR TG600MEF



Product price:

**2.579,00 € tax excluded**

## Product description:

### TELAIR TG600MEF CHARGER

TELAIR TG600MEF is a battery charger with more than double the charging capacity of a fuel cell or 100W solar panel Fully automatic.

The operation of the TELAIR TG600MEF charger is fully automatic, it is guaranteed by a combustion engine powered by the **LPG** on board, fuel with low environmental impact.

Thanks to a thick soundproof insulation, the TELAIR TG600MEF charger has an extremely low noise diffusion (only 51 dBA (7mt)) and almost imperceptible. The technical solutions adopted guarantee safe operation at all times, with negligible noise and vibrations.

System to manage **controlled** the **parallel** between the **motor battery** and the **service battery**.

The TELAIR TG600MEF charger starts when the battery is low (11.9V) and stops when it is full (14.5V). Useful when the engine battery is not completely efficient or when using high absorption electrical equipment

The TELAIR TG600MEF is charger with a simple and practical gas operation, just connect it to the gas bottle already present in the motorhome and it is ready to use

TELAIR TG600MEF is charger with a practical control panel that indicates high temperature and low oil level. In addition, the control panel is equipped with an indicator light that indicates all phases of ECOENERGY operation.

In addition, the panel is equipped with a button for forced manual start. It is used if you wish to switch on the ECOENERGY even if the battery voltage is above the minimum threshold level of 11.9 Volts. Once the 14.5 Volt voltage is reached, the ECOENERGY automatically switches the

engine off and goes back into stand-by again.

## **TECHNICAL FEATURES OF TELAIR TG600MEF CHARGER CHARACTERISTICS**

Automatic operation: Start 11.9V - Stop 14.5V

Operating temperature with propane gas: +50°C ÷ -25°C

Rated current: 25 A/h (480 A/24h)

Gas consumption/hour 290 g/h

Electrical power supply: Propane gas

Load voltage: 12V

Lubricating oil consumption: 1 lt/115 h

Noise at 7 mt LpA: 52 dBA

Weight 19 Kg

Length without brackets: 565 mm

Width without brackets: 380 mm

Height without brackets: 250 mm

Recommended batteries: 160 ÷ 300 Ah

Current supplied selectable: fixed

High mountain drive 2300 mt: NO

Connection cable with control unit 5 mt

Are you looking for a product with different characteristics? [HERE](#) you can find the entire TELAIR range and other specialist brands.

Images and technical data of TELAIR TG600MEF are not binding and may be modified by the manufacturer

### **Product features:**

Fuel: Gas

Output voltage (V): 12

Nominal current (A): 25 A/h (600 A/24h)

Gas consumption (Kg/h): 0,29

Acoustic pressure: 52 dB(A) at 7 m

Length (mm): 565

Width (mm): 380

Height (mm): 250