



# GENMAC Whisper-GAS G12000KS-M5 LPG GENERATOR 12,3KVA

## Product description:

GENMAC Whisper-GAS G12000KS-M5 LPG THREE-PHASE GENERATOR 12,3KVA

The generator Genmac Whisper-GAS G12000KS-M5 LPG three-phase is equipped with a Kohler motor powered by LPG gas capable of delivering 12,3KVA power with capacitor voltage regulator (AVR optional).

High quality professional silenced three-phase LPG power generator, Genmac with 12.3KVA power. The Genmac LPG generator is equipped with an oversized air-cooled Kohler motor.

Genmac professional LPG generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

This feature is fundamental to guarantee a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

## AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving performance and durability.

The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Whisper-GAS G12000KS-M5

---

## LPG 12,3KVA

Voltage regulator : capacitor (AVR Optional)

Power supply: LPG

Firing: Electric

Phase type: Single phase / Three phase

Singlephase continuous power: 3.7KVA / 3KW

Maximum singlephase power: 4.1KVA / 3.3KW

ThreePhase Continuous Power: 11.1KVA / 8.9KW

ThreePhase Maximum Power: 12.3KVA / 9.8KW

Motor: Kohler CH730

Socket Frame: 1 x Schuko 16A 230V / 1 x 32A 230V / 1 x 32A 400V

Voltage: 230 / 400 V

Frequency: 50 Hz

Emissions Standard: Stage V

3000 revolutions per minute

Autonomy @ 75%: 5.2 h fixed revolutions

Acoustic pressure: 65 dB(A) @ 7m

Length (mm): 1100

Width (mm): 540

Height (mm): 924

Dry weight (Kg): 257

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

### Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 3.3

Continuous power single phase (KW): 3

Maximum power single phase (KVA): 4.1

Continuous power single phase (KVA): 3.7

Maximum power three phase (KW): 9.8

Continuous power three phase (KW): 8.9

Maximum power three phase (KVA): 12.3

Continuous power three phase (KVA): 11.1

Fuel: LPG

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x Schuko 16A 230V / 1 x 32A 230V / 1 x 32A 400V

---

Engine: Kohler CH730  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Cooling: Air  
Poles: 2  
LPG consumption (m<sup>3</sup>/h): 5.2  
Acoustic pressure: 65 dB(A) at 7 m  
Length (mm): 1100  
Width (mm): 540  
Height (mm): 924  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: Capacitor / AVR (optional)  
Engine manufacturer: Kohler