

# GENMAC ROYAL G200CS-E3 THREE-PHASE 200 KVA DIESEL - MOTOR CUMMINS STAGE 3A

### **Product description:**

Ø.

## GENMAC ROYAL G200CS-E3

The GENMAC ROYAL G200CS-E3 is a 200 KVA super-silenced single-phase/three-phase diesel generator with Stamford alternator and AVR voltage regulator.

Thanks to its diesel fuel supply, the GENMAC ROYAL G200CS-E3 can only consume 4.5 m<sup>3</sup>/h at full load and has a low environmental impact, making it one of the best in its class.

The long life and reliability of the GENMAC ROYAL G200CS-E3 is due to a special control procedure during the various stages of production.

The GENMAC ROYAL G200CS-E3 is suitable for applications in different contexts such as: hospitals, industries, shopping malls, hotels, airports, banks, universities, stadiums, offices, etc.

The Stage 3A engine allows the use of the generator set also for mobile use, for example for roadworks and rental services.

## **Control panel features**

#### QT2A-4520

Self-standing tower with IP65 metal boxCircuit breakerAMF controller DSE4520- Voltmeter, Frequencymeter, Ammeter- Generator power (kW, kV Ar, kV A & pf) monitoring- Hour meter-Fuel level meter- Overload (kW & kV Ar) protection- Low oil pressure protection- High coolant temperature protection- Low fuel level protection- Battery charger alternator fault- Rpm protectionEmergency stop buttonAudible alarmTerminal board for ATS connectionCan Bus reading Port (if standard on the engine)Battery chargerOn/off switch

Images and technical data are not binding.

PrestaShop

R

#### **Product features:**

Ø.

Phase: Single phase / Three phase Maximum power three phase (KW): 176 Continuous power three phase (KW): 160 Maximum power three phase (KVA): 220 Continuous power three phase (KVA): 200 Fuel: Diesel Frequency (Hz): 50 Voltage (V): 230 / 400 **Emissions Regulations: Stage 3A** Engine rpm (rpm): 1500 Speed governor: Electronic Engine capacity (cm<sup>3</sup>): 6 Number cylinders: 6 Oil capacity (L): 18 Cooling: Water Alternator: Synchronous, self-excited Length (mm): 3600 Width (mm): 1226 Height (mm): 2000 Dry weight (Kg): 2224 AVR: Yes Silenced: Yes Super silenced: Yes Product type: Generator ATS Switch device : No Voltage regulator: AVR Engine manufacturer: Cummins

