



# PRAMAC P18000 SINGLE PHASE DPP



Product price:

**10.061,25 € tax excluded**

## Product description:

PRAMAC P18000 Single Phase 12.9 KW Super Silent Generator

The PRAMAC P18000 single-phase generator with 12.9 KW power, powered by a diesel engine running at 3000 RPM. The PRAMAC P18000 generator is equipped with electric start. The alternator of the PRAMAC P18000 generator is brushless with a capacitor voltage regulator. The Yanmar diesel engine makes the P18000 generator highly reliable as it is built and designed using top-quality materials and provides access to all components by opening the roof (which locks and unlocks with a safety key).

The PRAMAC P12000 can be chosen with or without AVR.

Thanks to its casing, this generator is super silent. The PRAMAC P18000 single-phase generator is suitable for outdoor use in small construction sites or for small outdoor jobs.

## Technical Specifications of the PRAMAC P18000 Single Phase Generator:

Maximum Single Phase Power: 12.92 KW

Continuous Single Phase Power: 12.46 KW

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Engine: Yanmar 3TNV76-HPGE

Start: Electric

Consumption: 6.21 Lt/h

Dimensions: Length: 1500 mm

Width: 754 mm

Height: 1032 mm

Weight: 455 Kg



**Outlets:**

1 SCHUKO 230V 16A IP68

1 2P+T CEE 230V 16A IP67

2 2P+T CEE 230V 32A IP67

The PRAMAC P18000 power generator is a professional diesel generator developed by Pramac with the features and equipment necessary to achieve a superior class product. The PRAMAC P18000 generator, with its low noise level, is the ideal generator for use in residential areas or outside working hours. The P18000 generator is equipped with a reliable diesel engine, top-quality components, and complete instrumentation.

If you are looking for a generator like the single-phase P18000 power generator, we recommend browsing our catalog of ground generators to find the one that best suits your needs.

Images and technical data are indicative only.

**Product features:**

Phase: Single phase

Maximum power single phase (KW): 12.92

Continuous power single phase (KW): 12.46

Maximum power single phase (KVA): 14.36

Continuous power single phase (KVA): 13.84

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A 2P+T CEE - 2 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar 3TNV76

Emissions Regulations: Stationary Use

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 1116

Oil capacity (L): 4.4

Cooling: Water



---

Alternator: Brushless  
Poles: 2  
Fuel tank capacity (L): 51  
Consumption (L/h): 6.21  
Running time (h): 8.21  
Acoustic power: 96 dB(A)  
Acoustic pressure: 67 dB(A) at 7 m  
Length (mm): 1500  
Width (mm): 754  
Height (mm): 1032  
Dry weight (Kg): 455  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: Capacitor  
Engine manufacturer: Yanmar