



CUMMINS C170 D5 THREE-PHASED DIESEL POWER GENERATOR 155KVA SILENCED

Product price:

24.035,00 € tax excluded

Product description:

CUMMINS C170 D5 Control system

Generator set control PowerStart 600

The PowerStart control is a microprocessor-based generator set monitoring and control system. The control provides a simple operator interface to the generator set, auto/ manual and remote start/stop control and shutdown fault indication. The integration of all control functions into a single control provides enhanced reliability and performance compared to conventional generator set control systems. This control has been designed and tested to meet the harsh environment in which gensets are typically applied.

- The PowerStart generator set control is suitable for use on a wide range of generator sets in nonparalleling applications. It is suitable for use with reconnectable or non-reconnectable generators, can be configured for either 50 Hz or 60 Hz and voltage and power connection from 190-600 VAC line-to-line.
- This control includes an intuitive operator interface that allows for complete genset control as well as system metering, fault annunciation, maintenance alarm, over imbalance current, configuration and diagnostics. The interface includes seven generator set status LED lamps with both internationally accepted symbols and English text to comply with customer needs. The interface also includes an LED backlit LCD display with tactile-feel softswitches for easy operation and screen navigation. The manual/auto/stop switch function is integrated into the interface panel.
- All data on the control can be viewed by scrolling through screens with the navigation keys. The control displays the current active fault and a timeordered history of the five previous faults.





- Power for this control is derived from the generator set starting batteries and functions over a voltage range from 8VDC to 16 VDC.

Product features:

Phase: Three phase

Maximum power three phase (KW): 136

Continuous power three phase (KW): 124

Maximum power three phase (KVA): 170

Continuous power three phase (KVA): 153

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: Terminal box

Engine: TCL 6BTAA5.9-G7

Emissions Regulations: Stage 3A

Engine rpm (rpm): 1500

Speed governor: Mechanical

Number cylinders: 6

Cylinders' position: In line

Cooling: Air

Poles: 4

Bore x stroke (mm): 91.4x127

Fuel tank capacity (L): 448

Consumption (L/h): 31.54 at 75% load

Running time (h): 14.2 at 75% load

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3460

Width (mm): 1090

Height (mm): 2387

Dry weight (Kg): 2390

Silenced: Yes

Super silenced: Yes

Product type: Generator

Control unit: PowerStart 600

ATS Switch device : Optional

Engine manufacturer: TCL

Precision of voltage regulation: $\pm 2,5\%$

