

LATHE OPTIMUM TU 2004V



Product description:

LATHE OPTIMUM TU 2004V

LATHE OPTIMUM TU 2004V with continuous speed adjustment and digital display.

TECHNICAL FEATURES OF THE OPTIMUM TU 2004V LATHE

Product type : Lathe

Tip height: 100 mm

Diam. turning on pallet: 200mm

Distance between points: 300 mm

Spindle speed, infinitely adjustable: 150 - 2500 rpm

Lathe speed number: 2

Spindle cone: cm 3

Bar passage: diam. 21 cm

Pallet width: 100 mm

Upper slide stroke: 55 mm

Cross slide stroke: 75 mm

Tailstock cone: cm 2

Tailstock-tailstock stroke: 65 mm

Longitudinal lathe feed: 0.1 to 0.2 mm/revolution

Metric threading: from 0.25 to 3 mm/revolution

Thread inches: 44 - 8 threads/1".

Length: 830 mm

Width: 425 mm

Height: 360 mm

Weight: 61 Kg.

lathe motor power: 600 W 230 V - 50 Hz

images and technical data not binding



Product features:

Phase: Single phase

Frequency (Hz): 50

Voltage (V): 230

Power (KW): 0.6

Length (mm): 830

Width (mm): 425

Height (mm): 360

Product type: Lathe

Weight (Kg): 61

