



## Storage System Leonardo Off-Grid 1500/24 GE

### Product description:

#### Storage System Leonardo Off-Grid 1500/24 GE

Leonardo Off-Grid 1500/24 GE is a storage system designed and developed specifically for the production and storage of domestic energy; combined with photovoltaic modules and Lithium storage batteries, Leonardo Off-Grid 1500/24 GE provides power to the home until its complete self-sustainability. The Leonardo Off-Grid 1500/24 GE makes it easy and immediate the use of energy produced by photovoltaic modules, for the supply of domestic users, with the help of a generator (back-up) in case of reduced renewable energy. The Leonardo Off-Grid 1500/24 GE system provides four independent MPPT inputs through a dedicated charge regulator: this technology implements a research circuit of maximum power depending on the voltage and current of the PV module, always maximizing the energy supplied. By connecting a generator set to the AC input, the Leonardo Off-Grid 1500/24 GE system guarantees the continuity of operation of the utilities without perceptible discontinuity in case of low battery due to the reduced renewable energy available. In fact, the genset manages simultaneously the power supply of the loads and the charging of the battery bank.

The Leonardo Off-Grid 1500/24 GE is equipped with an AC-OUT alternating current output line and an AC-IN alternating current input line. Since the device is equipped with an earth connection of the NEUTRO - TT system conductor, the AC-OUT AC output line can be protected with an AC-type thermal-magnetic circuit breaker, with rated current  $I_n=16A$  and differential current  $I_d=0.03A$  (this circuit breaker is usually already present in the distribution board of the house as protection against indirect contacts, with 30mA differential current). The AC-IN alternating current input line can be protected with an AC-type thermal-magnetic circuit breaker, with rated current  $I_n=16A$  and differential current  $I_d=0.3A$ , this circuit breaker can be inserted in an additional main switchboard or, if possible, in the existing distribution board in the dwelling.

You can discover the full range of storage systems on the dedicated section of the site by clicking [HERE](#).



---

Images and technical data not binding

**Product features:**

Frequency (Hz): 50

Voltage (V): 230

Protection degree: IP20

Length (mm): 315

Width (mm): 750

Height (mm): 130

Battery voltage (V): 24

Weight (Kg): 14

Output power (VA): 1500

Transfer time Inverter Bypass (ms): 10

Overload threshold: 85%

Efficiency: 94

Self-consumption on stand-by: 10 W

Switching threshold Inverter Mode / Bypass Mode (V): 23

Switching Threshold Bypass Mode/ Inverter Mode (V): 27.2

Internal over-temperature alarm: 65%

Operating temperature range (°C): 25°

