



CGM C7000E



Product price:

1.987,50 € tax excluded

Product description:

CGM C7000E single-phase generating set 7 KVA

Generator CGM C7000E single-phase 7 KVA set with Honda engine powered by STAGE V gasoline at 3000 rpm, compact and easy to use, mounted on a fixed base with rubber vibration dampers.

The CGM C7000E generator set is composed of a Made in Italy alternator from Linz or NSM, self-excited without brushes and with AVR voltage regulator. The CGM C7000E generator set is equipped with electric start with 12 V battery or manual recoil starter with recoil starter and with a low fuel consumption, in fact it consumes only 2 liters/hour at 75% of the load.

This generator is perfect for outdoor use as for example for hobby use. The CGM C7000E generating set is part of the CLASSIC series and is easily adaptable to various uses such as homes, mobile facilities, camping, hobbies, construction sites etc..

The C7000E generator set at 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

Technical specifications of CGM C7000E generator set:

Phase type: Single phase

Maximum single phase power: 6.9 KW

Maximum single phase continuous use power: 6.3 KW

Maximum single phase power: 7.7 KVA

Single-phase continuous use power: 7.7 KVA

Fuel: Gasoline

Voltage: 230 V

Frequency: 50 Hz

Engine: HONDA GX390



Engine RPM: 3000 RPM
Start: Electric
Voltage regulator system: AVR
Consumption: 2 Lt/h at 75% load
Tank capacity: 6. 1 Lt
Autonomy: 3 h at 75% load
Length: 780 mm
Width: 510 mm
Height: 500 mm
Weight: 82 Kg

Discover the full range reserved for Ground generators of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 6.9
Continuous power single phase (KW): 6.3
Maximum power single phase (KVA): 7.7
Continuous power single phase (KVA): 7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A 3P CEE - 1 x 230V 32A 3P CEE
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 389
Number cylinders: 1
Alternator: Made in Italy
Poles: 2
Fuel tank capacity (L): 6.1
Consumption (L/h): 2
Running time (h): 3
Length (mm): 780
Width (mm): 510

Height (mm): 500

Dry weight (Kg): 82

Silenced: No

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Honda