



# CGM C11000TE



Product price:

**2.850,00 € tax excluded**

## Product description:

CGM C11000TE Three-phase generator 10KVA

CGM C11000TE Three-phase generator 10KVA with Briggs & Stratton engine powered by STAGE V gasoline at 3000 rpm, compact and easy to use, mounted on a fixed base with rubber vibration dampers.

The CGM C11000TE is composed of a Made in Italy Linz or NSM alternator, self-excited with brushes and with AVR voltage regulator.

The CGM C11000TE generator is equipped with electric start with 12V battery but also with manual recoil starter and with a low fuel consumption, in fact it consumes only 2,2 liters/hour at 75% of the load for an autonomy up to 3 hours of operation. This CGM C11000TE generator set is perfect for outdoor use such as hobby use.

The CGM C11000TE generator is part of the CLASSIC series and is easily adaptable to a variety of uses such as homes, mobile facilities, campgrounds, hobbies, construction sites etc. The CGM C11000TE generator set at 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

## Technical features of CGM C11000TE:

Type of phase: Singlephase / Threephase

Maximum singlephase power: 3.6 KVA / 3 KW

Continuous singlephase power: 3.3 KVA / 2.6 KW

Maximum threephase power: 11 KVA / 8.8 KW

Continuous threephase power: 10 KVA / 8 KW

Fuel: Petrol

Voltage: 230/400 V



Frequency: 50 Hz  
Motor: BRIGGS & STRATTON 16HP  
Motor RPM: 3000 RPM  
Boosting: Electric  
Voltage regulator system: AVR  
Consumption: 3.8 Lt/h at 75% load  
Tank capacity: 8.5 Lt  
Autonomy: 2.2 h at 75% load  
Length: 910 mm  
Width: 580 mm  
Height: 640 mm  
Weight: 125 Kg

Discover the full range reserved for generators of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 3  
Continuous power single phase (KW): 2.6  
Maximum power single phase (KVA): 3.6  
Continuous power single phase (KVA): 3.3  
Maximum power three phase (KW): 8.8  
Continuous power three phase (KW): 8  
Maximum power three phase (KVA): 11  
Continuous power three phase (KVA): 10  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE  
Engine: Briggs&Stratton  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 480  
Number cylinders: 2  
Alternator: Made in Italy  
Poles: 2



---

Fuel tank capacity (L): 8.5  
Consumption (L/h): 3.8  
Running time (h): 2.2  
Length (mm): 910  
Width (mm): 580  
Height (mm): 64  
Dry weight (Kg): 125  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Briggs&Stratton

