



CGM DS4000T

Product price:

4.400,00 € tax excluded

Product description:

Three-phase CGM DS4000T generator set 4 KVA Supersilenced

CGM DS4000T three-phase 4 KVA generator set with a Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, equipped with enclosure that lowers noise emissions and makes it **super-silenced**.

The CGM DS4000T is composed of a Made in Italy alternator from Linz or NSM, self-excited with brushes and with AVR voltage regulator. The CGM DS4000T generator set is equipped with electric start with 12 V battery and with a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of the load. This CGM DS4000T is perfect for outdoor use.

The CGM DS4000T is part of the QUIET series and are characterized by lower fuel consumption and a longer life expectancy than the gasoline-powered range and equipped with soundproof cabin suitable for installation and outdoor use, and increased fuel tank. The CGM DS4000T generator set at 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

Technical features of CGM DS4000T:

Phase type: Three phase
Maximum power: 3.5 KW
Continuous power: 3.2 KW
Maximum power: 4.4 KVA
Continuous power: 4 KVA
Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Motor: KOHLER KD15-350
Engine speed: 3000 rpm
Starter: Electric



Voltage regulator system: AVR
Consumption: 1 Lt/h at 75% of the load
Tank capacity: 30 Lt
Autonomy: 30 h at 75% load
Length: 1100 mm
Width: 650 mm
Height: 900 mm
Weight: 160 Kg
Supersilenced

Discover the full range reserved for generator of CGM or other top brands browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Three phase
Maximum power three phase (KW): 3.5
Continuous power three phase (KW): 3.2
Maximum power three phase (KVA): 4.4
Continuous power three phase (KVA): 4
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 400
Sockets configuration: 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE - 1 x 230V SCHUKO
Engine: Kohler KD 15-350
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 349
Number cylinders: 1
Alternator: Made in Italy
Poles: 2
Fuel tank capacity (L): 30
Consumption (L/h): 1
Running time (h): 30
Length (mm): 1100
Width (mm): 650
Height (mm): 900
Dry weight (Kg): 160
Silenced: Yes
Super silenced: Yes

Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Kohler