



# **CLIMMA COMPACT 16 EH**

## Product price:

2.530,00 € tax excluded

## **Product description:**

Conditioner CLIMMA Compact 16EH Electrical heating

Independent air conditioner Climma Compact 16EH perfect to condition a single room or contiguous environments.

The Climma Compact 16EH air conditioner is specially designed for marine applications, just as all air conditioners in the Climma Compact range are water cooled. Compact, quiet and powerful, the Climma Compact 16EH air conditioner works with environmentally friendly refrigerant and comes with the option of cycle reversal to heat the environment.

The Climma Compact 16 air conditioner is also available in cold only or electrically heated version.

This version of the Climma Compact 16EH air conditioner is electrical heating.

For multiple installations with two or more air conditioners, a replay box is also available to use a single sea water pump.

## Technical characteristics of the Climma Compact 16EH air conditioner:

Phase type: Single-phase

Voltage: 230 V Frequency: 50 Hz

Cold capacity: 16000 BTU/h Heat capacity: 7000 BTU/h

Duct size: 150 mm

Maximum air flow: 900 m<sup>3</sup>/h

Length: 605 mm Width: 368 mm Height: 352 mm Weight: 46 Kg

### Main advantages:

- Independent air conditioning systems from 3500 to 27000 BTU/h





- Ecological refrigerant R410A for maximum efficiency and minimal consumption
- High efficiency ultra-fine gas-air cooler
- Powered and movable fan
- Pre-wired electrical box
- Threaded brass condensate drain and anti-condensation tray with Climma Dry Pan system
- High efficiency condenser

#### R410a

Ecological refrigerant that does not contain toxic chemicals that damage the ozone layer.

More efficient cooling system due to better heat exchange and less pressure drop. If you are looking for another air conditioner like the Climma Compact 16EH then you can browse our catalogue reserved for marine air conditioners.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase Frequency (Hz): 50 Voltage (V): 230

Maximum flow (m3/h): 900

Refrigerating yield: 16000 BTU/h Heating power: 16000 BTU/h

Length (mm): 605 Width (mm): 368 Height (mm): 352

Product type: Air conditioner

Coolant: R410A Weight (Kg): 46

