



# CGM S9000DUAL GENERATOR SINGLE PHASE / THREE PHASE 9KVA AVR STAGE V

Product price:

**1.582,50 € tax excluded**

## Product description:

CGM S9000DUAL GENERATOR SINGLE / THREE PHASE 9KVA AVR STAGE V

Generator CGM S9000DUAL with singlephase 7 KVA or threephase 9 KVA selector with CGM diesel powered STAGE V engine at 3000 rpm, compact and easy to use, equipped with enclosure that greatly reduces noise emissions and makes the CGM S9000DUAL **supersilenced**. The generator is composed of a self-excited alternator with brushes and a **AVR** voltage regulator.

The CGM S9000DUAL generator is a new model that allows you to have maximum power in both singlephase and threephase versions through a **practical single/threephase selector** located on the generator's socket panel. In this way, thanks to the power selector, you will be able to choose whether to use the power in singlephase 230 V or in threephase 400 V.

The generator is equipped with an electric start with a 12 V battery and a low fuel consumption, in fact it consumes only 2.1 liters/hour at 75% of the load for an autonomy of more than 6 hours of operation.

The generator is characterized by lower fuel consumption and a longer life expectancy than the gasoline range and equipped with soundproof cabin suitable for installation and outdoor use, and increased tank. The S9000DUAL generator at 3000 rpm is only suitable for emergency use for backup. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

## Technical specifications CGM S9000DUAL:

Phase type: Single / Threephase

Maximum singlephase power: 5.6 KW (7 KVA)

Maximum threephase power: 7. 2 KW (9 KVA)

Singlephase continuous use power: 5 KW (6.25 KVA)

Threephase continuous use power: 6.5 KW (8. 13 KVA)



Fuel: Diesel  
Voltage: 230 / 400 V  
Frequency: 50 Hz  
Motor: CGM  
Motor RPM: 3000 RPM  
Start: Electric  
Voltage regulator system: AVR  
Consumption: 2. 1 Lt/h at 75% load  
Tank capacity: 14 Lt  
Autonomy: 6.6 h at 75% load  
Length: 920 mm  
Width: 520 mm  
Height: 720 mm  
Weight: 162 Kg  
Super-silenced

Discover the full range reserved for Generators of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 5.6  
Continuous power single phase (KW): 5  
Maximum power single phase (KVA): 7  
Continuous power single phase (KVA): 6.25  
Maximum power three phase (KW): 7.2  
Continuous power three phase (KW): 6.5  
Maximum power three phase (KVA): 9  
Continuous power three phase (KVA): 8.13  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 32A 5P CEE - 1 x 230V 32A 3P CEE - 1 x 230V SCHUKO  
Engine: CGM 12HP  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 498  
Number cylinders: 1  
Alternator: With brushes



---

Poles: 2

