

GENERATOR MOSA GE 4000 MI



Product description:

MOSA GE4000MI CURRENT GENERATOR 4 KW SUPERSILENCED INVERTER

The generator singlephase MOSA GE4000MI 4KW is the new model set with Inverter technology for domestic, hobby and leisure use.

It is still quieter and more efficient than traditional models, the MOSA GE4000MI generator set delivers a stable and precise singlephase of 4KW suitable to sophisticated electronic equipment sensitive to voltage and frequency variations.

You can therefore safely and easily enjoy all the small comforts of home wherever you are: lights, fans, a coffee machine, laptops, radio or TV.

The compact size and light weight make the 4KW MOSA GE4000MI singlephase generator set extremely manageable and easy to transport thanks to the towing trolley with integrated wheels and removable telescopic handle.

The 12 Lt tank allows a continuous operation of more than 8 hours.

The safety of use is guaranteed by the overload protection and engine stop for low oil level.

The 4KW MOSA GE4000MI current generator can also be used in parallel, i.e. it can be connected to another equal generator in order to deliver twice the power.

The control panel of the 4KW generator includes two 230 V (16 A) home sockets, two USB ports and a 12 V (5 A) battery charging, radios, TVs, small appliances, laptops and tablets, mobile phones and much more.

Technical features:

Maximum singlephase power: 4KW

Continuous singlephase power: 3.6 KW

Maximum singlephase power: 4 KVA

Continuous singlephase power: 3.6 KVA

Fuel: Petrol

Voltage: 230 V

Frequency: 50 Hz

Motor: GK225 STAGE 5

Starter: Manual / Electric
Super-silenced 67 dB(A) at 7 metres
Length: 605 mm
Width: 432 mm
Height: 500 mm
Weight: 42 Kg
Inverter

If you are looking for another product like the MOSA GE4000MI generator then you can consult other earth current generators.

Images and data of the 4KW generator set are not binding and may be subject to review.

Product features:

Phase: Single phase
Maximum power single phase (KW): 4
Continuous power single phase (KW): 3.6
Maximum power single phase (KVA): 4
Continuous power single phase (KVA): 3.6
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 x 230V 16A 2P+T SCHUKO
Engine: GK225
Emissions Regulations: Stage 5
Engine rpm (rpm): 3600
Starting system: Manual / Electric
Engine capacity (cm³): 223
Number cylinders: 1
Alternator: Permanent magnets, self-excited, brushless
Fuel tank capacity (L): 12
Consumption (L/h): 1.4
Running time (h): 8.5
Acoustic power: 92 dB(A)
Acoustic pressure: 67 dB(A) at 7 m
Length (mm): 605
Width (mm): 432
Height (mm): 500
Dry weight (Kg): 42
Silenced: Yes
Super silenced: Yes
Product type: Generator

ATS Switch device : No
Voltage regulator: Inverter