



RIELLO SEP 2200 A3 2200 VA

Product description:

CHARACTERISTICS

Filtered, stabilised and reliable voltage: ON LINE double conversion technology (VFI according to IEC 62040-3) with filters for atmospheric noise suppression;

High overload capacity (up to 150%);

Programmable auto restart at mains return;

Battery ignition (Cold Start);

Load power factor correction (UPS input power factor close to 1);

Wide input voltage tolerance range (from 140 V to 276 V) without battery intervention;

Expandable autonomy for several hours;

Fully configurable via UPS Tools configuration software;

High battery reliability (automatic and manually activated battery test);

High UPS reliability (total microprocessor control);

Low impact on mains (sinusoidal absorption).

ADVANCED COMMUNICATION

Multiplatform communication for all operating systems and network environments: PowerShield3 monitoring and shutdown software for Windows 10, 8, 7, Hyper-V, 2019, 2016, 2012 and earlier versions, Mac OS X, Linux, VMWare ESXi, Citrix XenServer and other Unix operating systems;

UPS Tools configuration and customisation software supplied as standard;

RS232 serial port and opto-isolated contacts;

USB port;

Slot for communication cards.

Images and technical data are not binding.





Product features:

Phase: Single phase

Frequency (Hz): 50 / 60

Voltage (V): 220 / 230 / 240

Power (VA): 125000

Battery type: VRLA/AGM/GEL/NiCd/Liion/Supercaps

Operating temperature (°C): 0 °C / +40 °C

Length (mm): 446

Width (mm): 190

Height (mm): 333

Dry weight (Kg): 25.6

Colour: Black

