



# CGM PR5000TE



Product price:

**2.325,00 € tax excluded**

## Product description:

CGM PR5000TE Singlephase/Threephase generator set 5 KVA AVR

CGM PR5000TE is a **singlephase/threephase** 5 KVA generator set with **Honda engine** powered by **stage V** gasoline at 3000 rpm, compact and easy to use, mounted on a fixed base with vibration dampers. The CGM PR5000TE current generator is composed of a Made in Italy alternator from Linz or NSM, self-excited with brushes and with **AVR** voltage regulator. The CGM PR5000TE generator set is equipped with **electric start** with 12 V battery and with **low fuel consumption**, in fact it consumes only 1.6 liters/hour at 75% load. This CGM PR5000TE power generator is perfect for outdoor use such as hobby use.

The CGM PR5000TE power generator is part of the new PROFESSIONAL range which is the evolution of the DELUXE gasoline range. This power generator, like all those in the PROFESSIONAL series, is **robust and manageable**, specially designed for professionals and canters. These generators have a dedicated electrical panel with differential protection and a larger rainproof protective casing. The CGM PR5000TE generator set at 3000 rpm is **suitable only for emergency use**. It is not recommended to use it for more than 6 continuous hours and for more than 500 hours per year.

## The electrical panel is composed of:

- N.1 230V Schuko + N.1 230V 16A 3P CEE + N.1 400V 16A 5P CEE
- 12VDC socket
- Multimeter and hour meter
- Magnetothermal and differential switch

## Technical characteristics of the CGM PR5000TE:

Type of phase: Singlephase / Threephase

Maximum threephase power: 5.5 KVA / 4.8 KW

Continuous threephase power: 5 KVA / 4 KW



Maximum singlephase power: 1.8 KVA / 1.6 KW  
Singlephase continuous power: 1.6 KVA / 1.3 KW  
Fuel: Petrol  
Voltage: 230 V / 400 V  
Frequency: 50 Hz  
Engine: HONDA GX270  
& gt; Engine revolutions: 3000 rpm  
Starting: Electric  
Tank capacity: 15 Lt  
Consumption: 1.6 Lt / h at 75% of load  
Autonomy: 9.4 h at 75 % of the load  
Length: 825 mm  
Width: 550 mm  
Height: 530 mm  
Weight: 80 Kg

Discover the full range reserved for generator of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 1.6  
Continuous power single phase (KW): 1.3  
Maximum power single phase (KVA): 1.8  
Continuous power single phase (KVA): 1.6  
Maximum power three phase (KW): 4.8  
Continuous power three phase (KW): 4  
Maximum power three phase (KVA): 5.5  
Continuous power three phase (KVA): 5  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE - 1 x 230V SCHUKO  
Engine: Honda GX270  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 270

---

Number cylinders: 1  
Alternator: Made in Italy  
Poles: 2  
Fuel tank capacity (L): 15  
Consumption (L/h): 1.6  
Running time (h): 9.4  
Length (mm): 825  
Width (mm): 550  
Height (mm): 530  
Dry weight (Kg): 80  
Silenced: No  
Super silenced: No  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Honda