



CGM PR7000E



Product price:

2.462,50 € tax excluded

Product description:

CGM PR7000E Single-phase 7 KVA AVR generator

CGM PR7000E is a 7 KVA single-phase generator set with a Honda engine powered by STAGE V petrol at 3000 rpm, compact and easy to use, mounted on a fixed base with vibration dampers. The CGM PR7000E current generator consists of a Made in Italy alternator from Linz or NSM, self-excited with brushes and AVR voltage regulator.

The CGM PR7000E is equipped with an electric starter with 12 V battery and low fuel consumption, in fact it consumes only 2 litres/hour at 75% of the load. This CGM PR7000E power generator is perfect for outdoor use such as hobby use.

The CGM PR7000E is part of the new PROFESSIONAL range which is the evolution of the DELUXE petrol range. This power generator, like all those in the PROFESSIONAL series, is robust and easy to handle, designed specifically for professionals and singers. These generators are equipped with a dedicated electrical panel with differential protection and oversized rain cover.

The CGM PR7000E generator set at 3000 rpm is suitable for emergency use only. It is not recommended to use it for more than 6 hours continuously and for more than 500 hours per year.

The electric panel of the CGM PR7000E is composed of:

- N.1 230V Schuko + N.1 230V 16A 3P CEE + N.1 230V 32A 3P CEE
- 12VDC socket
- Multimeter and hour counter
- Thermal-magnetic and differential switch

Technical characteristics of the CGM PR7000E:



Phase type: Single-phase
Maximum single-phase power: 6.9 KW
Single-phase continuous power: 6.3 KW
Maximum single-phase power: 7.7 KVA
Single-phase continuous power: 7 KVA
Fuel: Petrol
Voltage: 230 V
Frequency: 50 Hz
Motor: HONDA GX390
Engine revs: 3000 rpm
Start-up: Electric
Tank capacity: 15 Lt
Consumption: 2 Lt/h at 75% of load
Autonomy: 7.5 h at 75% of the load
Length: 825 mm
Width: 550 mm
Height: 530 mm
Weight: 90 Kg
AVR

Discover the entire range reserved for CGM generators or other top brands by browsing our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 6.9
Continuous power single phase (KW): 6.3
Maximum power single phase (KVA): 7.7
Continuous power single phase (KVA): 7
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 1 x 230V 16A 3P CEE - 1 x 230V 32A 3P CEE - 1 x 230V SCHUKO
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 389
Number cylinders: 1
Alternator: Made in Italy



Poles: 2
Fuel tank capacity (L): 15
Consumption (L/h): 2
Running time (h): 7.5
Length (mm): 825
Width (mm): 550
Height (mm): 530
Dry weight (Kg): 90
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Honda

