



MARELLIMOTORI ALTERNATOR 410KVA MJB 315 MA4

Product description:

MARELLIMOTORI MJB 315MA4 ALTERNATOR 410KVA THREEPHASE

MARELLIMOTORI MJB 315MA4 is a three-phase alternator capable of delivering a power of **410KVA 328KW**, comes complete with AVR.

The frame of the alternator designed by MarelliMotori is equipped with side ribs to increase the resistance in addition the construction is made of strong welded steel

The 410KVA alternators MarelliMotori for continuous operation are designed to meet the vibration levels according to the standards, therefore they have a shielding in spheroidal cast iron or grey cast iron.

The shaft of the MJB 315MA4 is made of carbon steel and obtained by rolling. The shaft is obtained by forging from 290 mm diameter and is tested at the manufacturer in order to verify the absence of defects.

The stator/motor core of MarelliMotori is laminated and enamelled on both sides to minimize eddy current losses

The rotor of MJB 315MA4 is of salient pole type, made with class H flat copper wire insulated with enamel coating.

The winding is held by high quality steel through rods.

All MarelliMotori alternators are equipped with a large damping cage and are suitable for parallel operation with other generators, if equipped with the parallelization unit.

All MarelliMotori alternators can be designed to meet specific reactance values ($x'd$ and $x''d$).

The MarelliMotors alternators are all equipped with a voltage regulator, in the case of the analog MJB 315MA4. For the correct supply of voltage MARELLIMOTORI 410KVA has the need of an electronic control system, known as "voltage regulator" or "AVR" (acronym of Automatic Voltage Regulator). It guarantees the proper functioning of the machine and above all of the electrical



network behind it.

The AVR is an electronic device that converts alternating current with frequency and voltage variable over time into direct current and thus avoids current surges.

The AVR designed by MarelliMotori is internally equipped with a radio noise filter, which allows to contain radio noise emitted by MarelliMotori generators within the limits set by the European regulations for industrial environments

Select the alternator that reflects the **technical specifications you require**, visit our dedicated section to understand how.

TECHNICAL FEATURES OF THE THREE-PHASE 410KVA ALTERNATOR MJB 315MA4

Phase type: Three phase
Maximum power 50Hz: 410KVA
Maximum power 50Hz: 328KW
Maximum power 60Hz: 500KVA
Maximum power 60Hz: 400KW
Frequency: 50 - 60Hz
Voltage: 400V / 480V
Protection degree: IP23
A alternator speed: 1500 / 2250 rpm
Number of poles: 4
Yield: 95. 0%
Weight: 1060 Kg
Constant speed
AVR

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range **MARELLIMOTORI** and other specialized brands.

Images and technical data not binding and subject to change by the manufacturer

Product features:

Phase: Single phase / Three phase
Maximum power three phase (KW): 328
Maximum power three phase (KVA): 410
Frequency (Hz): 50 / 60
Voltage (V): 400
Engine rpm (rpm): 1500
Poles: 4

Efficiency (%): 95.0

Protection degree: IP23

Brushes: No

Type of alternator: Constant Speed

Voltage regulator: AVR

Weight (Kg): 1060