



HELVI SPEEDY 430

Product price:

254,70 € tax excluded

Product description:

HELVI SPEEDY430 Battery charger

HELVI SPEEDY430 is a battery charger with starter, portable with charge current selector, ammeter, thermostatic protection against long starts, internal fuse against short circuits and polarity reversal.

The HELVI SPEEDY430 battery charger is perfect for charging batteries with a 12 V or 24 V voltage and a 28 A current.

The HELVI SPEEDY430 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI SPEEDY430 battery charger are in the automotive, domestic and agricultural sectors.

HELVI SPEEDY430 is a single-phase battery charger with 230 V power supply and 50/60 Hz frequency. The HELVI SPEEDY430 battery charger has a rated power of 1000 W for a maximum current of 42 A.

The nominal charging capacity of the HELVI SPEEDY430 battery charger is 420 Ah and has 3 charging positions plus Boost.

HELVI SPEEDY430 is very compact and very light thanks to its weight of about 16 Kg.

Technical characteristics of the HELVI SPEEDY430 battery charger:

Phase type: Single-phase

Voltage: 230 V

Frequency: 50/60 Hz

Power: 1000 W

Battery voltage: 12/24 V

Maximum current: 42 A

Charging current: 28 A

Maximum surge current: 380 Acc

Charging capacity: 420 Ah 15h

Charging positions: 3 + Boost

Length: 245 mm



Width: 250 mm
Height: 435 mm
Weight: 16.2 Kg

If you are looking for another product similar to the HELVI SPEEDY430 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Product features:

Phase: Single phase
Frequency (Hz): 50 / 60
Voltage (V): 230
Power (W): 1000
Adjustment positions: 3 + Boost
Nominal current (A): 28
Charge capacity (Ah): 420
Battery voltage (V): 12 / 24
Charging voltage (V): 12 / 24
Current max (A): 42
Length (mm): 245
Width (mm): 250
Height (mm): 435
Product type: Battery Charger
Weight (Kg): 16.2