



HELVI AUTOSTAR 1300

Product price:

1.539,90 € tax excluded

Product description:

HELVI AUTOSTAR1300 Battery charger

HELVI AUTOSTAR1300 is a battery charger with portable starter equipped with selector switch and ammeter to adjust and display the charge current level. HELVI AUTOSTAR1300 is protected with internal fuse against short circuits or polarity reversal and thermostatic protection against prolonged starts. HELVI AUTOSTAR1300 is equipped with C.P.S. (car protection system) able to activate and deactivate the start function (boost) totally automatically, to protect the electronics on board the vehicle.

The HELVI AUTOSTAR1300 battery charger is perfect for charging batteries with a 12 V or 24 V voltage and 80 A current.

The HELVI AUTOSTAR1300 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI AUTOSTAR1300 battery charger are in the automotive, construction and agricultural sectors.

HELVI AUTOSTAR1300 is a single-phase/three-phase battery charger with 230/400 V power supply and 50/60 Hz frequency. The HELVI AUTOSTAR1300 battery charger has a nominal power of 2900 W for a maximum current of 120 A.

The nominal charging capacity of the HELVI AUTOSTAR1300 charger is 1200 Ah and has 12 charging positions plus Boost.

HELVI AUTOSTAR1300 is very compact and comfortable to transport thanks to its wheels despite its weight of 69 kg.

Technical characteristics of the HELVI AUTOSTAR1300 battery charger:

Phase Type: Single/Triphase

Voltage: 230/400 V

Frequency: 50/60 Hz

Power: 2900 W

Battery voltage: 12/24 V

Maximum current: 120 A

Charging current: 80 A





Maximum surge current: 1300 Acc
Charging capacity: 1200 Ah 15h
Charging positions: 12 + Boost
Length: 330 mm
Width: 575 mm
Height: 770 mm
Weight: 69.2 Kg

If you are looking for another product similar to the HELVI AUTOSTAR1300 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Frequency (Hz): 50 / 60
Voltage (V): 230 / 400
Power (W): 2900
Adjustment positions: 12 + Boost
Nominal current (A): 80
Charge capacity (Ah): 1200
Battery voltage (V): 12 / 24
Charging voltage (V): 12 / 24
Current max (A): 120
Length (mm): 330
Width (mm): 575
Height (mm): 770
Product type: Battery Charger
Weight (Kg): 69.2

