

RIMOR VFR130 2R2G1Z INVERTER SINGLEPHASE 2,2KW IP54



Product description:

INVERTER VFR130 2R2G1Z SINGLEPHASE 2,2KW IP54

The inverter VFR130 2R2G1Z of 2,2KW power with IP54 protection rating is a voltage and frequency converter capable of generating a voltage and frequency controlled three-phase system to make it possible to vary the speed of asynchronous or vector motors.

The Inverter VFR130 2R2G1Z is equipped with a display for reading and programming with the possibility to activate a very large number of functions, to satisfy every industrial application.

The application of inverters to the various operating machines (pumps, fans, conveyor belts, mills, etc.) allows to obtain a real energy saving, as only the actual power needed is consumed. In fact, the starting by inverter is done by absorbing the actual necessary current, so it is not necessary to take into account the high inrush currents present in case of starting with other systems.

The 2,2KW inverter has an IP54 housing and is equipped with filters for cooling air inlet and outlet. This requirement allows keep the internal inverter unit particularly clean, limiting the deposit of dirt on the heat sink, boards and internal components.

Therefore, the Rimor IP54 inverter is a simple, robust and reliable piece of equipment, containing the classic Rimor IP23 standard inverter inside, which is shielded and cooled in the most appropriate way. This solution guarantees reduced maintenance, longer life and greater reliability of the inverter.

The abbreviation IP corresponds to International Protection Rating and, following the IEC 60529 standard, identifies the degrees of shielded of the enclosures for electrical devices.

This standard was also created to avoid an excessive use of vague terms, such as "waterproof". Thanks to the IP protection class it is instead possible to be more exhaustive and precise, clearly

defining to what extent the device is shielded against the intrusion of solid and liquid bodies, dust and possible accidental contact.

TECHNICAL CHARACTERISTICS OF SINGLE-PHASE INVERTER VFR130 2R2G1Z IP54

Input Voltage: 220V

Working power: 2,2KW

Overload: 150%

Maximum output frequency: 500 Hz

Min. operating temperature: -10.00 °C

Max working temperature: 40.00 °C

Protection class: IP54

Length: 250 cm

Width: 300 cm

Height: 400 cm

If you are looking for an Inverter with other features or more power than 2,2KW then we suggest you to browse our wide catalogue

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power three phase (KW): 2.2

Voltage (V): 220 - 240

Protection degree: IP54

Length (mm): 2500

Width (mm): 3000

Height (mm): 4000