



GENMAC Combi RG7300HO-M5 GENERATOR 7,1KVA

Product price:

1.239,00 € tax excluded

Product description:

GENMAC Combi RG7300HO-M5 GENERATOR 7,1KVA

The generator Genmac Combi RG7300HO-M5 single phase has a Honda gasoline powered engine capable of delivering a power of 7,1KVA with the possibility of connection to optional AVR.

The Genmac RG7300HO-M5 single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 6.1 liters for an autonomy of about three and a half hours, complete with manual recoil starter.

The generator is very light and makes it very easy to move for other uses, in addition for an even easier and more dynamic portability is possible the optional supply of a practical transport kit dedicated to this line of generators.

The Genmac 7,1KVA generator is portable of professional quality and you can ask for the supply with AVR.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 7,1KVA Genmac Combi RG7300HO-M5

Power Supply: Gasoline



Starting: Manual recoil
Phase Type: Single Phase
Continuous Power: 6.4KVA / 5.8KW
Maximum Power: 7.1KVA / 6.4KW
Motor: Honda GX390
Emission Standard: Stage V
Voltage: 230V
Frequency: 50 Hz
3000 rpm
Fuel tank: 25 Lt.
Autonomy @ 75%: 12 h fixed rpm
Sound pressure: 72 dB (A) @ 7 m
Starting: Manual
Length (mm): 780
Width (mm): 540
Height (mm): 560
Dry weight (Kg): 81

If you are looking for another product then you can consult on our catalog other terrestrial generator.

Images and technical data are not binding and may be subject to review

Product features:

Phase: Single phase
Maximum power single phase (KW): 6.4
Continuous power single phase (KW): 5.8
Maximum power single phase (KVA): 7.1
Continuous power single phase (KVA): 6.4
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Engine: 4 stroke
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Pull starter
Cooling: Air
Fuel tank capacity (L): 25
Running time (h): 12
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 780
Width (mm): 540

Height (mm): 560

Dry weight (Kg): 81

Product type: Generator

ATS Switch device : No

Voltage regulator: AVR (optional)