



# HELVI GALILEO 219

Product price:

**343,44 € tax excluded**

## Product description:

HELVI GALILEO219 Welding machine

HELVI GALILEO219 is an easy to use single-phase inverter welding machine with excellent welding characteristics with all types of commercial electrodes (rutile, basic, stainless steel). HELVI GALILEO219 is equipped with overvoltage, overtemperature and electrode bonding control. HELVI GALILEO219 is equipped with a STICK/TIG selector (lift arc) and can be powered by generator sets and long connection lines. HELVI GALILEO219 is ideal for light carpentry and maintenance work.

HELVI GALILEO219 is a single-phase welding machine with 230 V power supply and 50/60 Hz frequency. The HELVI GALILEO219 welding machine has a rated power of 60% of 6000 W for a maximum current of 200 A.

The HELVI GALILEO219 welding machine is designed for MMA and TIG welding with electrodes ranging from 1.6 mm to 5 mm in diameter.

The no-load voltage of the HELVI GALILEO219 welding machine is 48 V and has a current regulation from 5 A up to 200 A.

The HELVI GALILEO219 welding machine has H insulation and IP23S protection.

HELVI GALILEO219 is very compact and extremely light thanks to its weight of about 6 Kg. Thanks to its comfortable handle it is also easy to transport to where you need it most.

## Technical characteristics of the HELVI GALILEO219 welding machine:

Phase type: Single-phase

Frequency: 50/60 Hz

Voltage: 230 V

Power: 6000 W

Type of welding: MMA / TIG

Open-circuit voltage: 48 V

Current regulation: 5 - 200 A

Duty cycle at 40°: 200 A at 60% - 155 A at 100%

Maximum current: 200 A



Electrode diameter: 1.6 - 5 mm  
Electrode type: 6013 - 7018  
Insulation: H  
Degree of protection: IP23S  
Length: 370 mm  
Width: 140 mm  
Height: 245 mm  
Weight: 6.7 Kg

If instead you are looking for another product similar to the HELVI GALILEO219 welding inverter, then we recommend you look at the entire range dedicated to welding machines.

Images and technical data are not binding.

**Product features:**

Phase: Single phase  
Frequency (Hz): 50 / 60  
Voltage (V): 230  
Protection degree: IP23S  
Power (W): 6000  
Motor insulation class: H  
No-load voltage (V): 48  
Regulation current (A): 5 - 200  
Welding current (A): 200 at 60% - 155 at 100%  
Diameter electrodes (mm): 1.6 - 5  
Type of welding: MMA / MIG  
Current max (A): 200  
Length (mm): 370  
Width (mm): 140  
Height (mm): 245  
Product type: Welding machine  
Weight (Kg): 6.7