



# GENMAC Combipro G7900HAC-M5 GENERATOR 8,0KVA

Product price:

**2.409,00 € tax excluded**

## Product description:

GENMAC COMBIPRO G7900HAC-M5 TRHEE-PHASE GENERATOR 8,0KVA

The generator Genmac Combipro G7900HAC-M5 three phase is equipped with a Honda gasoline powered engine capable of delivering a power of 8,0KVA with capacitor voltage regulator (AVR optional).

The Generators of the **Genmac Combipro G7900 series** are among the most **silent** in their category, thanks to the side closing panels and the oversized muffler.

These power generators are built with a **compact and robust** structure with sturdy **wheels and handle** integrated into the frame, which makes them handy and easily transportable. The 300mm diameter wheels with double reinforcement, with which Combipro generators are equipped, are integrated in the structure and the retractable handle can be folded to avoid unnecessary hindrance when not in use. On the frontal part there is also a full length support to avoid sinking into the ground.

The front panel of the Genmac 8,0KVA generator is protected by a canopy and comes complete with a back panel that provides **water protection and insulation**.

The Genmac G7900 8,0KVA generators are equipped with a **25-liter tank** with a large cap that is convenient to unscrew even with work gloves, filter and **fuel level indicator**. There is also a manual fuel circuit shut-off tap to prevent fuel leakage.

The Genmac Combipro mounts a **Honda OHV 4-stroke petrol engine**. They are very reliable engines that guarantee efficient combustion and **low fuel consumption**. The engines with 7,1KVA generators are also equipped with a protection system that causes the **engine to stop if the oil level is too low**.

TECHNICAL FEATURES OF GENERATOR GENMAC COMBIPRO G7900HAC-M5 8,0KVA





Voltage regulator : capacitor (AVR Optional)  
Power supply: Gasoline  
Firing: Electric  
Phase type: Singlephase / Threephase  
Singlephase continuous power: 2.4KVA / 2.2KW  
Maximum singlephase power: 2.7KVA / 2.4KW  
Threephase continuous power: 7.3KVA / 5.8KW  
Threephase maximum power: 8.0KVA / 6.4KW  
Motor: Honda iGX390  
Socket panel: 1 x schuko 230V - 1 x 16A 230V - 1 x 16A 400 V  
Emission standard: Stage V  
Voltage: 230 / 400V  
Frequency: 50 Hz  
3000 revolutions per minute  
Tank: 25 Lt.  
Autonomy @ 75%: 14 h fixed revolutions  
Start: Manual  
Length (mm): 800  
Width (mm): 640  
Height (mm): 700  
Dry weight (Kg): 122

If you are looking for another product then you can see on our catalog other generator

Images and technical data not binding.

#### Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 2.4  
Continuous power single phase (KW): 2.2  
Maximum power single phase (KVA): 2.7  
Continuous power single phase (KVA): 2.4  
Maximum power three phase (KW): 6.4  
Continuous power three phase (KW): 5.8  
Maximum power three phase (KVA): 8  
Continuous power three phase (KVA): 7.3  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO  
Engine: Honda iGX390, 4 stroke, OHV





Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Starting system: Elettrico  
Cooling: Air  
Poles: 2  
Fuel tank capacity (L): 25  
Running time (h): 14  
Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 800  
Width (mm): 640  
Height (mm): 700  
Dry weight (Kg): 122  
Silenced: Yes  
Super silenced: No  
ATS Switch device : Yes  
Voltage regulator: AVR (optional)  
Engine manufacturer: Honda

