



GENMAC Combiplus G6700KEO GENERATOR 7,0KVA

Product price:

2.555,00 € tax excluded

Product description:

GENMAC Combiplus G6700KEO THREE-PHASE GENERATOR 7,0KVA

The generator Genmac Combiplus G6700KEO three phase is equipped with a Kohler Diesel powered engine capable of delivering a power of 7,0KVA with capacitor voltage regulator (AVR optional).

Genmac Diesel professional high quality diesel generators, are equipped with a Kohler engine, which generates a continuous power of 6,3kva in only 3000 rpm and a maximum limited power (L.T.P.) of 7,0KVA . The engine is cooled by a fan, favoring and allowing a prolonged use of the generator without running the risk of overheating the mechanical parts that compose it.

Genmac professional diesel generators are highly reliable machines, built with quality components to be used in the professional field, where reliability is fundamental.

This feature is fundamental to ensure a high reliability of the generator, reduces its effort and increases its life span by lowering the noise level.

The 7,0KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All models in the Genmac Combipro series are available with optional AVR voltage regulator. The AVR is a device that allows to **maintain the output more constant and less load-dependent**. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

The model equipped with AVR card is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable



with common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you can enjoy greater stability and thus increase the life of your devices.

TECHNICAL FEATURES OF GENERATOR GENMAC Combiplus G6700KEO 7,0KVA

Voltage regulator : capacitor (AVR Optional)

Power supply: Diesel

Firing: Electric

Phase type: Single phase / Three phase

Single phase continuous power: 2.1KVA / 1.9KW

Maximum single phase power: 2.3KVA / 2.1KW

Three-phase continuous power: 6.3KVA / 5.0KW

Three-phase maximum power: 7.0KVA / 5.6KW

Motor: Kohler KD440

Socket panel: 1 x Schuko 16A 230V - 1 x 16A 400V

Voltage: 230 / 400 V

Frequency: 50 Hz

3000 rpm

Tank: 19 Lt.

Autonomy @ 75%: 14 h fixed

Starting: Manual

Length (mm): 810

Width (mm): 550

Height (mm): 680

Dry weight (Kg): 121

If you are looking for another product then you can see on our catalog other generator.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KW): 1.9

Maximum power single phase (KVA): 2.3

Continuous power single phase (KVA): 2.1

Maximum power three phase (KW): 5.6

Continuous power three phase (KW): 5

Maximum power three phase (KVA): 7

Continuous power three phase (KVA): 6.3

Fuel: Diesel

Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x Schuko 16A 230V - 1 x 16A 400V
Engine: Kohler KD 440
Engine rpm (rpm): 3000
Starting system: Electric
Cooling: Air
Poles: 2
Fuel tank capacity (L): 19
Running time (h): 14
Length (mm): 810
Width (mm): 550
Height (mm): 680
Dry weight (Kg): 121
ATS Switch device : Optional
Voltage regulator: AVR (optional)
Engine manufacturer: Kohler