



GENMAC Combiflash RG201HEO-M5 MOTOSALDATOR 7,1KVA

Product price:

2.043,00 € tax excluded

Product description:

GENMAC Combiflash RG201HEO-M5 SINGLE-PHASE MOTOR WELDER 7,1KVA

The Genmac Combiflash RG201HEO-M5 singlephase motor welder is equipped with a Honda GX390 Stage V gasoline engine capable of delivering a power of 7,1KVA.

This engine Motorwelder is ideal for having electrical current always at hand in any place and environment (construction sites, markets, beaches, camping sites or for first aid in difficult areas), combined with a powerful electrode welder.

The small size and moderate weight of the singlephase 7.1KVA Genmac Combiflash RG201HEO-M5 motorwelder make it one of the most popular professional products in the Genmac line.

Fitted with a Honda GX390 engine capable of delivering a power of 7.1KVA with gasoline supply and an "air" cooling system using a fan, guaranteeing maximum efficiency and durability even for long and continuous work as both a motor welding machine and a welder. The Generator generates a maximum power of 7.1KVA at just 3000 rpm.

These characteristics make the Genmac MotorWelder one of the most appreciated products on the market for its high quality/price ratio.

All the mechanical and electrical components that make up the Chainsaw, are positioned inside a metal frame, which protects the delicate parts from shocks or foreign bodies that could damage it. This frame also allows easy transportation and positioning of the Motor Welding Machine by the users, facilitating their loading and unloading.

The start-up of the Motowelder singlephase 7.1KVA Genmac Combiflash RG201HEO-M5, by means of an automatic electrical system.

His lightness and the possibility to request a mobilization kit, is very appreciated by those customers who deal with repairs on streets or squares and that for reasons of lack or remoteness of parking for their own car, they must carry the generator by hand for considerable distances (old town, uncomfortable areas, etc.)

In the lateral part the electric motorwelder, is provided of 1 current exit with attack type SCHUKO from 230V 16A and 1 of the type CEE from 230V 32A suitable to the connection of any electric apparatus of common use.

TECHNICAL CHARACTERISTICS OF THE MOTOR WELDER GENMAC Combiflash RG201HEO-M5 7,1KVA

Power Supply: Gasoline

Firing: Electric

Phase Type: Single Phase

Maximum Power: 7.1KVA / 6.4KW

Welding Current: 60 - 200 A

Maximum Welding Current: 200 A ac

Service (A): 200 - 35% / 180 - 60%

Welding Type: Electrode

Voltage: 230V

Frequency: 50 Hz

Motor: Honda GX390

Emission Standard: Stage V

Socket panel: 1 x Schuko 16A 230V / 1 x 32A 230V

3000 rpm

Tank: 19 Lt.

Autonomy @ 75%: 9 h fixed rpm

Length (mm): 810

Width (mm): 550

Height (mm): 680

Dry weight (Kg): 113

If you are looking for another product then you can consult on our catalog other Motor Welders.

Images and technical data are not binding.

Product features:

Phase: Single phase

Maximum power single phase (KW): 6.4

Maximum power single phase (KVA): 7.1

Fuel: Gasoline

Frequency (Hz): 50
Voltage (V): 230
Engine: Honda GX390
Emissions Regulations: Stage 5
Engine rpm (rpm): 3000
Starting system: Electric
Cooling: Air
Poles: 2
Welding current (A): 200 - 35% / 180 - 60%
Type of welding: MMA
Current max (A): 200
Fuel tank capacity (L): 19
Running time (h): 9
Length (mm): 810
Width (mm): 550
Height (mm): 680
Dry weight (Kg): 113
Silenced: Yes
Super silenced: No
Voltage regulator: No
Engine manufacturer: Honda