



GENMAC Combiflash G250KEO MOTOSALDATOR 8,8KVA

Product price:

5.090,00 € tax excluded

Product description:

GENMAC Combiflash G250KEO THREE-PHASE MOTOR WELDER 8,8KVA

The Genmac Combiflash G250KEO three-phase motor welder is equipped with a Kohler KD425/2 Diesel engine capable of delivering a power of 8.8KVA.

This motorwelder is ideal for having electrical current always at hand in any place and environment (construction sites, markets, beaches, camping sites or for first aid in uncomfortable areas), combined with a powerful electrode welder.

The small size and moderate weight of the three-phase 8.8KVA Genmac Combiflash G250KEO motorwelder make it one of the most popular professional products in the Genmac line.

These features make the Genmac Combiflash G250KEO motorwelder, one of the most appreciated products on the market for its high quality/price ratio.

All the mechanical and electrical components that make up the welder are positioned inside a metal frame, which protects the delicate parts from shocks or foreign bodies that could damage it. This frame also allows for easy transportation and positioning of the welder by users, making it easier for them to load and unload.

The start-up of the motorwelder Genmac Combiflash G250KEO, is via an automatic electric start module.

The lightness of the machine and the possibility of requesting a mobilization kit, is very appreciated by those customers who deal with repairs on streets or squares and who, for reasons of lack or distance of parking for their cars, have to carry the machine by hand for considerable distances (historical center, uncomfortable areas, etc.).



In the lateral part the motorwelder, it is equipped with 1 current output with attack type 230V 16A and 1 of the CEE type 400V 32A suitable for the connection of any electrical appliance of common use.

TECHNICAL CHARACTERISTICS MOTOR WELDER GENMAC Combiflash G250KEO 8,8KVA

Power Supply: Diesel

Firing: Electric

Phase Type: SinglePhase / ThreePhase

Maximum SinglePhase Power: 3KVA / 2.3KW

Maximum ThreePhase Power: 8. 8KVA / 7KW

Welding Current: 40 - 250 A

Maximum Welding Current: 300 A ac

Service (A): 250 - 35% / 200 - 60%

Welding Type: Electrode

Voltage: 230 / 400 V

Frequency: 50 Hz

Motor: Kohler KD425/2

Socket panel: 1 x 16A 230V / 1 x 32A 400 V

3000 rpm

Tank: 19 Lt.

Autonomy @ 75%: 14 h fixed rpm

Length (mm): 870

Width (mm): 620

Height (mm): 690

Dry weight (Kg): 185

If you are looking for another product then you can consult our catalog other Motor Welder.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 2.3

Maximum power single phase (KVA): 3

Maximum power three phase (KW): 7

Maximum power three phase (KVA): 8.8

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: Kohler KD 425/2

Engine rpm (rpm): 3000



Starting system: Electric

Cooling: Air

Poles: 2

Welding current (A): 250 - 35% / 200 - 60%

Type of welding: MMA

Current max (A): 300

Fuel tank capacity (L): 19

Running time (h): 14

Length (mm): 870

Width (mm): 620

Height (mm): 690

Dry weight (Kg): 185

Silenced: Yes

Super silenced: No

Voltage regulator: No

Engine manufacturer: Kohler

