



# EGM ISB2000-SE GENERATOR 2KW



Product price:

**675,68 € tax excluded**

## Product description:

### EGM ISB2000-SE SINGLEPHASE GENERATOR 2KW

The Generator EGM ISB2000-SE **singlephase features** a gasoline-powered engine capable of delivering a power output of **2KW** with an Inverter Voltage Regulator.

The EGM ISB2000-SE singlephase generator provides reliable power for home, business and recreational environments. Safely powering appliances and other electronic devices. Power solution for outdoor parties. This generator set is compact and extremely reliable, featuring manual recoil start with self-winding.

The EGM ISB2000-SE generator is equipped with a switch that will allow you to adjust the intensity of the load according to your needs, so if you do not have the need for maximum power output, you can save fuel.

The 2KW generator has a convenient double-curved handle that can be folded for easy mobility and storage. Equipped with dual USB inputs, the generator is extremely quiet and fuel efficient with a 79.7 cc OHV engine.

It has two access doors to make it easy to change the oil, air filter or drain the carburetor.

### TECHNICAL FEATURES OF THE SINGLEPHASE GENERATOR EGM ISB2000-SE 2KW

Phase Type: SinglePhase  
Maximum Output: 2KW  
Continuous Output: 1.6KW  
Stationing: Fixed  
Power Supply: Gasoline  
Starting: Manual  
Displacement: 79 cc  
Voltage: 230 V



Frequency: 50 Hz  
Runtime at 50% load: 6 h  
Tank Capacity: 4. 2l  
Acoustic power: 59 dB(A) @ 7m  
Automatic voltage regulation: Inverter  
Length (mm): 545  
Width (mm): 330  
Height (mm): 505  
Dry weight (Kg): 22

If you are looking for another product then you can consult on our catalog other overland generators.

Images and technical data are not binding.

**Product features:**

Phase: Single phase  
Maximum power single phase (KW): 2  
Continuous power single phase (KW): 1.6  
Maximum power single phase (KVA): 2  
Continuous power single phase (KVA): 1.6  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Engine rpm (rpm): 3000  
Starting system: Manual recoil  
Poles: 2  
Acoustic pressure: 59 dB(A) at 7 m  
Length (mm): 545  
Width (mm): 330  
Height (mm): 505  
Dry weight (Kg): 22.1  
Silenced: Yes  
Super silenced: No  
ATS Switch device : No  
Voltage regulator: Inverter