



EGM ISB2000-SE GENERATOR 2KW



Product price:

675,68 € tax excluded

Product description:

EGM ISB2000-SE SINGLEPHASE GENERATOR 2KW

The Generator EGM ISB2000-SE **singlephase features** a gasoline-powered engine capable of delivering a power output of **2KW** with an Inverter Voltage Regulator.

The EGM ISB2000-SE singlephase generator provides reliable power for home, business and recreational environments. Safely powering appliances and other electronic devices. Power solution for outdoor parties. This generator set is compact and extremely reliable, featuring manual recoil start with self-winding.

The EGM ISB2000-SE generator is equipped with a switch that will allow you to adjust the intensity of the load according to your needs, so if you do not have the need for maximum power output, you can save fuel.

The 2KW generator has a convenient double-curved handle that can be folded for easy mobility and storage. Equipped with dual USB inputs, the generator is extremely quiet and fuel efficient with a 79.7 cc OHV engine.

It has two access doors to make it easy to change the oil, air filter or drain the carburetor.

TECHNICAL FEATURES OF THE SINGLEPHASE GENERATOR EGM ISB2000-SE 2KW

Phase Type: SinglePhase
Maximum Output: 2KW
Continuous Output: 1.6KW
Stationing: Fixed
Power Supply: Gasoline
Starting: Manual
Displacement: 79 cc
Voltage: 230 V



Frequency: 50 Hz
Runtime at 50% load: 6 h
Tank Capacity: 4. 2l
Acoustic power: 59 dB(A) @ 7m
Automatic voltage regulation: Inverter
Length (mm): 545
Width (mm): 330
Height (mm): 505
Dry weight (Kg): 22

If you are looking for another product then you can consult on our catalog other overland generators.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2
Continuous power single phase (KW): 1.6
Maximum power single phase (KVA): 2
Continuous power single phase (KVA): 1.6
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Engine rpm (rpm): 3000
Starting system: Manual recoil
Poles: 2
Acoustic pressure: 59 dB(A) at 7 m
Length (mm): 545
Width (mm): 330
Height (mm): 505
Dry weight (Kg): 22.1
Silenced: Yes
Super silenced: No
ATS Switch device : No
Voltage regulator: Inverter