



EGM GSD12000EP-SE GENERATOR 11KW



Product price:

4.525,50 € tax excluded

Product description:

EGM GSD12000EP-SE SINGLETHREEPHASE GENERATOR 11KW

The generator EGM GSD12000EP-SE Singlethreephase is equipped with a gasoline engine capable of delivering 11KW power with AVR voltage regulator.

The generator is easy to install and operate, as simple as starting and stopping thanks to clear and intuitive controls (electric start) Auto power off for low oil level Resistant chassis.

The 11KW Singlethreephase generator is equipped with bolted, heavy duty wheels and hinged handle to make it a robust and easy to carry. The recessed sockets with snap-on safety covers make it safer.

The 11KW generator is equipped with bolted, heavy duty wheels and hinged handle make it a robust and easy to transport. The recessed sockets with snap-on safety covers make it more secure.

The generator has a practical double-curved handle, which can be folded down for easy mobility and storage. EGM GSD12000EP-SE has an all-steel construction and a large metal tank with fill indicator. The generator guarantees an efficient and silent operation thanks to the OHV engine that allows to deliver a maximum power of 11KW.

TECHNICAL CHARACTERISTICS OF THE GENERATOR EGM GSD12000EP-SE 11KW

Phase Type: Single Phase / Three Phase

Maximum Output: 11 KW

Continuous Output: 10 KW

Voltage: 230 / 400 V

Frequency: 50 Hz

Autonomy at 50% load: 4h



Tank Capacity: 26l
Start: Electric
Engine Displacement: 870 cc
Power supply: Diesel
Outputs: 1x16A/230V, 1x32A/230V, DC 12V 8.3A
Sound pressure: 65 dB(A) @ 7 m
Voltage regulator: AVR
Length (mm): 1250
Width (mm): 670
Height (mm): 765
Dry weight (Kg): 235

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 11
Continuous power single phase (KW): 10
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Starting system: Electric
Poles: 2
Acoustic pressure: 65 dB(A) at 7 m
Length (mm): 1250
Width (mm): 670
Height (mm): 765
Dry weight (Kg): 235
Silenced: Yes
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR