



# GENMAC DAILY RG6000KS-M5 GENERATOR 6,2KVA

**Product price:**

**3.238,00 € tax excluded**

## **Product description:**

GENMAC DAILY RG6000KS-M5 SINGLE-PHASE GENERATOR 6,2KVA

The generator Genmac Daily RG6000KS-M5 single phase is equipped with a Kohler KD15-440 Stage V motor powered by diesel capable of delivering a power of 6,2KVA with capacitor voltage regulator (AVR optional).

High quality professional silenced single-phase diesel power generator, Genmac with 6,2KVA power. The Genmac diesel generator is equipped with an oversized air-cooled Kohler motor.

Genmac professional diesel generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

The Stage V engine allows the use of the generator set also for mobile use, for example for road construction sites and rental services. The generator is suitable for applications in different contexts such as: hospitals, industries, shopping centers, hotels, airports, banks, universities, stadiums, offices, etc..

All Kohler engines are built using the best materials, the most innovative techniques and the most advanced quality control methods.

Each engine is thoroughly tested to prove that it works perfectly before delivery.

In case of need, Kohler service is always at your disposal.

The 6,2KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

## AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load.



The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

#### TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily RG6000KS-M5 6,2KVA

Voltage regulator : capacitor (AVR Optional)  
Power supply: Diesel  
Starting: Electric  
Phase type: Single phase  
Continuous power: 5.6KVA / 5.0KW  
Maximum power: 6.2KVA / 5.6KW  
Motor: Kohler KD15-440  
Emissions regulation: Stage V  
Receptacle panel: 1 x 16A 230V - 2 x 32A 230V  
Voltage: 230V  
Frequency: 50 Hz  
3000 rpm  
Tank capacity: 19 l  
Autonomy @ 75%: 14 h fixed rpm  
Sound pressure @7m: 69dBa  
Length (mm): 1030  
Width (mm): 620  
Height (mm): 804  
Dry weight (Kg): 200

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 5.6  
Continuous power single phase (KW): 5  
Maximum power single phase (KVA): 6.2  
Continuous power single phase (KVA): 5.6  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230



Sockets configuration: 1 x 16A 230V - 2 x 32A 230V

Engine: Kohler KD 15-440

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Cooling: Air

Poles: 2

Fuel tank capacity (L): 19

Running time (h): 14

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 200

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Kohler

