



GENMAC DAILY RG6000KS-M5 GENERATOR 6,2KVA

Product price:

3.238,00 € tax excluded

Product description:

GENMAC DAILY RG6000KS-M5 SINGLE-PHASE GENERATOR 6,2KVA

The generator Genmac Daily RG6000KS-M5 single phase is equipped with a Kohler KD15-440 Stage V motor powered by diesel capable of delivering a power of 6,2KVA with capacitor voltage regulator (AVR optional).

High quality professional silenced single-phase diesel power generator, Genmac with 6,2KVA power. The Genmac diesel generator is equipped with an oversized air-cooled Kohler motor.

Genmac professional diesel generators are highly reliable machines, built with quality components to be used in professional field, where reliability is fundamental.

The Stage V engine allows the use of the generator set also for mobile use, for example for road construction sites and rental services. The generator is suitable for applications in different contexts such as: hospitals, industries, shopping centers, hotels, airports, banks, universities, stadiums, offices, etc..

All Kohler engines are built using the best materials, the most innovative techniques and the most advanced quality control methods.

Each engine is thoroughly tested to prove that it works perfectly before delivery.

In case of need, Kohler service is always at your disposal.

The 6,2KVA generator is equipped with a capacitor voltage regulator, on request it can be supplied with the AVR regulator.

AVR Voltage Regulator

All Genmac series models are available with optional AVR voltage regulator. The AVR is a device that allows to keep the output more constant and less dependent on the load.



The model equipped with AVR board is highly recommended, as it guarantees a significant improvement in the stability of the output; this feature makes the generators particularly suitable for common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you will enjoy greater stability and therefore an increase in the life of your devices.

TECHNICAL CHARACTERISTICS OF GENERATOR GENMAC Daily RG6000KS-M5 6,2KVA

Voltage regulator : capacitor (AVR Optional)
Power supply: Diesel
Starting: Electric
Phase type: Single phase
Continuous power: 5.6KVA / 5.0KW
Maximum power: 6.2KVA / 5.6KW
Motor: Kohler KD15-440
Emissions regulation: Stage V
Receptacle panel: 1 x 16A 230V - 2 x 32A 230V
Voltage: 230V
Frequency: 50 Hz
3000 rpm
Tank capacity: 19 l
Autonomy @ 75%: 14 h fixed rpm
Sound pressure @7m: 69dBa
Length (mm): 1030
Width (mm): 620
Height (mm): 804
Dry weight (Kg): 200

If you are looking for another product then you can consult other terrestrial generators in our catalog.

Images and technical data are not binding.

Product features:

Phase: Single phase
Maximum power single phase (KW): 5.6
Continuous power single phase (KW): 5
Maximum power single phase (KVA): 6.2
Continuous power single phase (KVA): 5.6
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230



Sockets configuration: 1 x 16A 230V - 2 x 32A 230V

Engine: Kohler KD 15-440

Emissions Regulations: Stage 5

Engine rpm (rpm): 3000

Starting system: Electric

Cooling: Air

Poles: 2

Fuel tank capacity (L): 19

Running time (h): 14

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 1030

Width (mm): 620

Height (mm): 804

Dry weight (Kg): 200

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional

Voltage regulator: Capacitor / AVR (optional)

Engine manufacturer: Kohler

