

# TELWIN ENERGY 1000 START 230-400V 12-24V



## Product description:

TELWIN ENERGY1000 START CHARGER 230-400V 12-24V 2,5KW

Telwin Energy1000 Start is a battery charger and starter with a power of 2,5KW for charging free electrolyte (WET) and lead acid (START&STOP) batteries with a voltage of 12/24V.

The **2,5KW battery charger** Telwin Energy1000 allows the quick start of all types of cars, vans, light trucks, construction equipment and trucks.

The Telwin charger gives the possibility to select **3 modes: normal, quick (BOOST) and finally quick start**, according to the user's need.

Telwin Energy1000 is equipped with fast charging timer. Equipped with protection systems both against overloads and for polarity reversals. Equipped with display for current charge. Equipped with remote control.

Telwin Energy1000 is a 2,5KW battery charger with high performance and comfortable both in transport and use thanks to the handle and wheels that make it handy and easy to move. Ideal for both the demanding hobbyist and the professional, being a versatile, high performance and reliable product. The Telwin Energy1000 charger has a voltage of 12/24V and its maximum output current is 1000A and the charging power is 2,5KW. It has a maximum capacity of 1200Ah, its dimensions are 380x560x885 mm while its weight is 45kg. Standard is equipped with two clamps, one mass and one positive and a remote control. TECHNICAL CHARACTERISTICS OF THE BATTERY CHARGER 2,5KW TELWIN ENERGY1000 START

Phase Type: Single/Triphase

Mains voltage Three-phase: 230 V/ 400V

Frequency: 50 / 60 Hz

Charging power: 2.5 KW

Starting power: 20 KW

Charging voltage: 12 / 24 V  
Effective charging current: 100 A  
Charging current EN60335-2-29: 80 A  
Current rating 1v/c EN60335-2-29: 640 A  
Maximum starting current: 1000 A  
Nom.ref.min. capacity: 20 Ah  
Nom.ref.max. capacity: 1200 / 800 Ah  
Adjustment positions: 5  
Length: 36.5 cm  
Width: 56 cm  
Height: 88.5 cm  
Weight: 45 Kg

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range **TELWIN** and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer

**Product features:**

Phase: Single phase / Three phase  
Frequency (Hz): 50 / 60  
Voltage (V): 230 / 400  
Power (W): 10000  
Effective current (A): 90  
Adjustment positions: 5  
Charging voltage (V): 12 / 24  
Length (mm): 380  
Width (mm): 560  
Height (mm): 885  
Dry weight (Kg): 45  
Overload protectors: Yes  
Video: 2I3AIIWsa3c