



HELVI EASYMIG 238

Product price:

1.096,20 € tax excluded

Product description:

HELVI EASYMIG238 Welding machine

HELVI EASYMIG238 is a portable, wheeled, three-phase continuous wire welding machine. HELVI EASYMIG238 is equipped with torch with Euro connection, pressure reducer, gas pipe, clamp and ground cable, timer for spot welding. The reel holder allows to use reels from 5 to 15 Kg. HELVI EASYMIG238 and 208N are ideal for bodywork and light carpentry.

HELVI EASYMIG238 is a single-phase / three-phase welding machine with 230 V / 400 V power supply and 50/60 Hz frequency. The HELVI EASYMIG238 welder has a power rating of 60% of 5900 W for a maximum current of 240 A.

The HELVI EASYMIG238 welding machine is designed for MIG and MAG welding for wires of different materials:

- steel (diameter from 0.6 mm to 1 mm)
- stainless steel (diameter from 0.8 mm to 1 mm)
- aluminium (diameter from 0.8 mm to 1 mm)

The no-load voltage of the HELVI EASYMIG238 welder ranges from 17 V to 38 V and has a current regulation from 30 A up to 240 A.

The 40° working cycle of the HELVI EASYMIG238 welder is 230 A at 35% and 175 A at 60%.

The HELVI EASYMIG238 welding machine has H insulation and IP22S protection.

HELVI EASYMIG238 is very compact and convenient to transport. Despite its weight of about 67 kg it is easy to manoeuvre thanks to the wheels and the handle on top.

Technical characteristics of the HELVI EASYMIG238 welding machine:

Phase type: Single-phase / Three-phase

Frequency: 50/60 Hz

Voltage: 230/400 V

Power: 5900 W

Type of welding: MIG / MAG

Open-circuit voltage: 17 - 38 V



Current regulation: 30 - 240 A
Duty cycle at 40°: 230 A at 35% - 175 A at 60%
Maximum current: 240 A
Adjustment positions: 7
Steel welding wire diameter: 0.6 - 1 mm
Stainless steel welding wire diameter: 0.8 - 1 mm
Aluminium welding wire diameter: 0.8 - 1 mm
Insulation: H
Degree of protection: IP22S
Length: 770 mm
Width: 465 mm
Height: 660 mm
Weight: 67 Kg

If instead you are looking for another product similar to the HELVI EASYMIG238 welding inverter, then we recommend you look at the entire range dedicated to welding machines.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Frequency (Hz): 50 / 60
Voltage (V): 230 / 400
Protection degree: IP22S
Power (W): 5900
Motor insulation class: H
No-load voltage (V): 17 - 38
Adjustment positions: 7
Regulation current (A): 30 - 240
Welding current (A): 230 at 35% - 175 at 60%
Ø steel welding wire (mm): 0.6 - 1
Ø inox welding wire (mm): 0.8 - 1
Ø aluminium welding wire (mm): 0.8 - 1
Type of welding: MIG-MAG
Current max (A): 240
Length (mm): 770
Width (mm): 465
Height (mm): 660
Product type: Welding machine
Weight (Kg): 67